

REMS Mini-Press 14 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. For battery and corded operation.

Pipe pressing joints \varnothing 10–40 mm $7 \varnothing \frac{3}{8} - 1 \frac{1}{4}$

Complete range of REMS pressing tongs Mini/pressing rings for all common pressfitting systems, see page 152–180.

REMS Mini-Press 14 V ACC – universal up to \varnothing 40 mm. Super light, super small, super handy. With automatic circuit control. Secure crimping in seconds. Automatic locking of the pressing tongs.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152–180). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 180.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.4 kg. Drive unit with pressing tongs V22 only 33 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Ergonomically designed housing. LED work light for illuminating the work place. Swivelling pressing tongs seat. Secure seating of pressing tongs/adapter tongs by automatic locking. Electronic charging status check with flat battery protection and charging status indicator with 2-coloured LED.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 14.4 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion PLUS technology. Highly resistant Li-Ion 14.4 V battery with 2.5 or 5.0 Ah capacity for long service life. Light and powerful. Li-Ion 14.4 V, 2.5 Ah batteries for approx. 275 pressings, 5.0 Ah for approx. 550 pressings Viega Profipress DN 15 with one battery charge*. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 220–240 V, 10.8–18 V, 65 W, for short charging times. Voltage supply 220–240 V/14.4 V, 33 A output, for mains operation instead of Li-Ion battery 14.4 V, as accessory.

Supply format

REMS Mini-Press 14 V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints \varnothing 10–40 mm, $\varnothing \frac{3}{8} - 1 \frac{1}{4}$ ". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14.4 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 14.4 V, 2.5 Ah, rapid charger 220–240 V, 50–60 Hz, 10.8–18 V, 65 W.

Version	Art.-No.
In sturdy steel case.	578012
In L-Boxx system case.	578013

Other voltages on request.

Accessories

Description	Art.-No.
REMS pressing tongs Mini/pressing rings see page 152–180.	
REMS cropping tongs Mini for threaded rods see page 181.	
REMS Mini-Press 14 V ACC drive unit, without battery	578001
Battery Li-Ion 14.4 V, 2.5 Ah	571545
Battery Li-Ion 14.4 V, 5.0 Ah	571555
Rapid charger 220–240 V, 50–60 Hz, 10.8–18 V, 65 W	571560
Voltage supply 220–240 V/14.4 V, 50–60 Hz, 33 A, for mains operation instead of battery Li-Ion 14.4 V.	571565
Steel case with inlay	578290
L-Boxx system case with inserts	578299



German Quality Product



* Ambient temperature approx. 20°C.

REMS Mini-Press 22 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22V Technology. For battery and corded operation.

Pipe pressing joints $\varnothing 10 - 40 \text{ mm} / \varnothing \frac{3}{8} - 1 \frac{1}{4}''$

Complete range of REMS pressing tongs Mini/pressing rings for all common pressfitting systems, see page 152–180.

REMS Mini-Press 22 V ACC – universal up to $\varnothing 40 \text{ mm}$. Super light, super small, super handy, ultra fast. Pressing under 4 s. Automatic pressing process. With automatic circuit control. Li-Ion 21.6 V, 2.5 Ah battery for approx. 390 pressings Viega Profipress DN 15 with one battery charge*.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152–180). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 180.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.5 kg. Drive unit with pressing tongs V15 only 31 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle $> 360^\circ$. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-Ion 21.6V, 2.5Ah batteries for approx. 390 pressings, 4.4 Ah for approx. 685 pressings, 5.0 Ah for approx. 780 pressings, 9.0 Ah for approx. 1400 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range -10 to $+60^\circ\text{C}$. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.



German Quality Product



Info



Supply format

REMS Mini-Press 22 V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints \varnothing 10–40 mm, \varnothing $\frac{3}{8}$ –1 $\frac{1}{4}$ ". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240 V or 110 V, 50–60 Hz, 70 W.

Version	Art.-No.
In sturdy steel case.	578010
In L-Boxx system case.	578014

Other voltages on request.

Accessories

Description	Art.-No.
REMS pressing tongs Mini/pressing rings see page 152–180.	
REMS cropping tongs Mini for threaded rods see page 181.	
REMS Mini-Press 22 V ACC drive unit, without battery	578002
Battery Li-Ion 21.6 V, 2.5 Ah	571571
Battery Li-Ion 21.6 V, 4.4 Ah	571574
Battery Li-Ion 21.6 V, 5.0 Ah	571581
Battery Li-Ion 21.6 V, 9.0 Ah	571583
Rapid charger 100–240 V, 50–60 Hz, 90 W	571585
Rapid charger 100–240 V, 50–60 Hz, 290 W	571587
Voltage supply 220–240 V/21.6 V, 50–60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567
Steel case with inlay	578290
L-Boxx system case with inserts	578299
REMS Lumen 2800 22 V, cordless LED flood light, see page 111	



REMS Mini-Press S 22 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22V Technology. For battery and corded operation.

Pipe pressing joints \varnothing 10–40 mm / \varnothing $\frac{3}{8}$ – $\frac{1}{4}$ "

Complete range of REMS pressing tongs Mini/pressing rings for all common pressfitting systems, see page 152–180.

REMS Mini-Press S 22 V ACC – universal up to \varnothing 40 mm. Super light, super small, super handy, ultra fast. Pressing under 4 s. Automatic pressing process. With automatic circuit control. Li-Ion 21.6V, 2.5 Ah battery for approx. 390 pressings Viega Profipress DN 15 with one battery charge*.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152–180). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 180.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.6 kg. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle $>360^\circ$. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-Ion 21.6V, 2.5 Ah batteries for approx. 390 pressings, 4.4 Ah for approx. 685 pressings, 5.0 Ah for approx. 780 pressings, 9.0 Ah for approx. 1400 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.



German Quality Product





Supply format

REMS Mini-Press S 22V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø 3/8–1 1/4". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240 V or 110 V, 50–60 Hz, 70 W.

Version	Art.-No.
In sturdy steel case.	578015
In L-Boxx system case.	578016

Other voltages on request.

Accessories

Description	Art.-No.
REMS pressing tongs Mini/pressing rings see page 152 – 180.	
REMS cropping tongs Mini for threaded rods see page 181.	
REMS Mini-Press S 22V ACC drive unit, without battery	578003
Battery Li-Ion 21.6 V, 2.5 Ah	571571
Battery Li-Ion 21.6 V, 4.4 Ah	571574
Battery Li-Ion 21.6 V, 5.0 Ah	571581
Battery Li-Ion 21.6 V, 9.0 Ah	571583
Rapid charger 100–240 V, 50–60 Hz, 90 W	571585
Rapid charger 100–240 V, 50–60 Hz, 290 W	571587
Voltage supply 220–240 V/21.6 V, 50–60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567
Steel case with inlay	578290
L-Boxx system case with inserts	578299
REMS Lumen 2800 22V, cordless LED flood light, see page 111	



for all common pressfitting systems

**Select REMS pressing tongs Mini/
REMS pressing rings yourself!**

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the REMS pressing tongs Mini/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Can be driven by all REMS radial presses 22 kN. Adapter tongs (page 180) required for driving REMS (PR) pressing rings.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

REMS pressing tongs Mini (PZ-2B)

REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

REMS Mini ACz, Fz, HEz, RFz, RFlz pressing tongs with teeth prevent formation of burr on the pressfitting (**Patent EP 2 027 971**).

REMS pressing ring S (PR-2B)

REMS pressing ring S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 180.

Traceability according to EN 1775:2007

REMS pressing tongs Mini with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.



German Quality Product



REMS Mini pressing tongs (PZ-2B)



REMS pressing ring S (PR-2B), continuously swivellable



Confirmation of suitability

See page 237.

Hold-Harmless and Indemnification Agreement

See page 238.





Pressing tongs with teeth prevent formation of burr on the pressfitting. Patent EP 2 027 971

Example REMS pressing tongs Mini V: "V" imprint on pressed fitting for traceability according to EN 1775:2007

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
A				
AC-FIX PRESS (Global Piping Systems)	H 12		578396	
	H 16		578400	
	H 20		578406	
	H 25		578408	
	H 32		578412	
	RFz 12		578490	
	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
	U 16		578374	
	U 20		578378	
	U 25		578380	
	U 32		578382	
	VX 16		578552	
	VX 20		578554	
	AC-FIX PRESS DUO (Global Piping Systems)	RFz 16		578492
RFz 20			578494	
RFz 25			578496	
RFz 32			578498	
TH 16			578352	
TH 20			578358	
TH 25			578360	
TH 26			578362	
TH 32			578364	
TH 16 S (PR-2B)		Mini Z8	574782	
TH 20 S (PR-2B)		Mini Z8	574788	
TH 26 S (PR-2B)		Mini Z8	574794	
TH 32 S (PR-2B)		Mini Z8	574798	
U 16			578374	
U 20			578378	
U 25			578380	
U 32			578382	
AC-FIX PRESS-MULTI (Global Piping Systems)	H 16		578400	
	H 18		578404	
	H 20		578406	
	H 25		578408	
	H 32		578412	
	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
	U 16		578374	
	U 18		578376	
	U 20		578378	
ACOME ACOPEX ALU	H 16		578400	
	H 20		578406	
	H 26		578410	
	H 32		578412	
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	U 16		578374	
	U 20		578378	
U 32		578382		
ACOME MT	ACz 12		578608	
	ACz 16		578610	
	ACz 20		578612	
	ACz 25		578614	
AHLSELL A-press elförzinkad M	M 12		578310	
	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 12 S (PR-2B)	Mini Z8	574736	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
M 28 S (PR-2B)	Mini Z8	574744		
M 35 S (PR-2B)	Mini Z8	574746		
AHLSELL A-press elförzinkad V	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	AHLSELL A-press koppar M	M 12		578310
		M 15		578312
		M 18		578314
M 22			578316	
M 28			578318	
M 35			578390	
M 12 S (PR-2B)		Mini Z8	574736	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
AHLSELL A-press koppar V	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
AHLSELL A-press rostfritt	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
AIRBEL PRESSCLIM	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
AIRBEL SERTINOX	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
ALB Sistema Multicapa	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
ALB Sistema Multicapa Gas	U 16		578374
	U 18		578376
	U 20		578378
	C 26		578392
	U 32		578382
	U 40		578386
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	H 16		578400
H 20		578406	
H 26		578410	
H 32		578412	
U 16		578374	
U 20		578378	
C 26		578392	
U 32		578382	
ALTECH Altech	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
APE MULTYGAS Serie AP Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
APE Serie AP	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	
U 16		578374	
U 20		578378	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
APE Serie APL	H 16		578400	ASSOTHERM IPC-RAC Carbon Steel	M 15		578312
	H 18		578404		M 18		578314
	H 20		578406		M 22		578316
	H 26		578410		M 28		578318
	H 32		578412		M 35		578390
	TH 16		578352		M 15 S (PR-2B)	Mini Z8	574738
	TH 18		578356		M 18 S (PR-2B)	Mini Z8	574740
	TH 20		578358		M 22 S (PR-2B)	Mini Z8	574742
	TH 26		578362		M 28 S (PR-2B)	Mini Z8	574744
	TH 32		578364		M 35 S (PR-2B)	Mini Z8	574746
	TH 40		578624				
	TH 16 S (PR-2B)	Mini Z8	574782	ASSOTHERM IPI-RAX Inox	M 15		578312
	TH 20 S (PR-2B)	Mini Z8	574788		M 18		578314
	TH 26 S (PR-2B)	Mini Z8	574794		M 22		578316
	TH 32 S (PR-2B)	Mini Z8	574798		M 28		578318
	U 16		578374		M 35		578390
	U 18		578376		M 15 S (PR-2B)	Mini Z8	574738
	U 20		578378		M 18 S (PR-2B)	Mini Z8	574740
			578378		M 22 S (PR-2B)	Mini Z8	574742
			578378		M 28 S (PR-2B)	Mini Z8	574744
		578378	M 35 S (PR-2B)		Mini Z8	574746	
AQUATECHNIK Press-fitting metal	H 16		578400	ASSOTHERM IPI-RAX Inox Gas	M 15		578312
	H 20		578406		M 18		578314
	H 26		578410		M 22		578316
	H 32		578412		M 28		578318
	TH 16		578352		M 35		578390
	TH 20		578358		M 15 S (PR-2B)	Mini Z8	574738
	TH 26		578362		M 18 S (PR-2B)	Mini Z8	574740
	TH 32		578364		M 22 S (PR-2B)	Mini Z8	574742
	TH 16 S (PR-2B)	Mini Z8	574782		M 28 S (PR-2B)	Mini Z8	574744
	TH 20 S (PR-2B)	Mini Z8	574788		M 35 S (PR-2B)	Mini Z8	574746
	TH 26 S (PR-2B)	Mini Z8	574794				
	TH 32 S (PR-2B)	Mini Z8	574798	ASSOTHERM IPM-Multistrato	H 16		578400
	U 16		578374		H 20		578406
	U 20		578378		H 26		578410
	C 26		578392		H 32		578412
	U 32		578382		TH 16		578352
			578468		TH 20		578358
			578472		TH 26		578362
			578474		TH 32		578364
			578476		THL 32		578368
		578456	TH 40			578624	
		578460	TH 16 S (PR-2B)	Mini Z8	574782		
		578462	TH 20 S (PR-2B)	Mini Z8	574788		
		578464	TH 26 S (PR-2B)	Mini Z8	574794		
		574728	TH 32 S (PR-2B)	Mini Z8	574798		
		574730	U 16		578374		
		574732	U 20		578378		
		574734	C 26		578392		
		578400	U 32		578382		
		578406					
		578410	ASSOTHERM IPR-RRR Copper	M 15		578312	
		578412		M 18		578314	
		578352		M 22		578316	
		578358		M 28		578318	
		578362		M 35		578390	
		578364		M 15 S (PR-2B)	Mini Z8	574738	
		574782		M 18 S (PR-2B)	Mini Z8	574740	
		574788		M 22 S (PR-2B)	Mini Z8	574742	
		574794		M 28 S (PR-2B)	Mini Z8	574744	
		574798		M 35 S (PR-2B)	Mini Z8	574746	
		578374					
		578378	ASSOTHERM IPR-RRR Copper Gas	M 15		578312	
		578392		M 18		578314	
		578382		M 22		578316	
				M 28		578318	
				M 35		578390	
				M 15 S (PR-2B)	Mini Z8	574738	
				M 18 S (PR-2B)	Mini Z8	574740	
				M 22 S (PR-2B)	Mini Z8	574742	
				M 28 S (PR-2B)	Mini Z8	574744	
				M 35 S (PR-2B)	Mini Z8	574746	
			ASTM F 1807 (Fittings with Copper Crimp Ring for PEX tubing)	US 3/8"		578534	
				US 1/2"		578536	
				US 3/4"		578538	
				US 1"		578540	
			ATUSA ITALIA SYCPRESS CARBON STEEL PRESS FITTINGS	M 15		578312	
				M 18		578314	
				M 22		578316	
				M 28		578318	
				M 35		578390	
			M 15 S (PR-2B)	Mini Z8	574738		
			M 18 S (PR-2B)	Mini Z8	574740		
			M 22 S (PR-2B)	Mini Z8	574742		
			M 28 S (PR-2B)	Mini Z8	574744		
			M 35 S (PR-2B)	Mini Z8	574746		
			ATUSA ITALIA SYCPRESS STAINLESS STEEL PRESS FITTINGS	M 15		578312	
				M 18		578314	
				M 22		578316	
				M 28		578318	
				M 35		578390	
				M 15 S (PR-2B)	Mini Z8	574738	
				M 18 S (PR-2B)	Mini Z8	574740	
				M 22 S (PR-2B)	Mini Z8	574742	
			M 28 S (PR-2B)	Mini Z8	574744		
			M 35 S (PR-2B)	Mini Z8	574746		
Aschl NIR	M 15		578312				
	M 18		578314				
	M 22		578316				
	M 28		578318				
	M 35		578390				
	M 15 S (PR-2B)	Mini Z8	574738				
	M 18 S (PR-2B)	Mini Z8	574740				
	M 22 S (PR-2B)	Mini Z8	574742				
	M 28 S (PR-2B)	Mini Z8	574744				
	M 35 S (PR-2B)	Mini Z8	574746				

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
AUSTEC PEX-B, PEX-AL-PEX (AUS)	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
AUSTEC PEX-AL-PEX GAS (AUS)	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
AYOR FIXOCONNECT Press	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	Rfz 12		578490
	Rfz 16		578492
	Rfz 20		578494
	Rfz 25		578496
	U 16		578374
	U 20		578378
	U 25		578380
AYOR FIXOMULTIX	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 20		578378
U 32		578382	
U 40		578386	
AYOR SOMATHERM FOR YOU -1	H 16		578400
	H 20		578406
	H 26		578410
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	U 16		578374
U 20		578378	
AYOR SOMATHERM FOR YOU -2	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	Rfz 12		578490
	Rfz 16		578492
	Rfz 20		578494
	Rfz 25		578496
	U 16		578374
	U 20		578378
U 25		578380	
B			
Bampi BALPEX serie LP	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 18		578376
	U 20		578378
	C 26		578392
U 32		578382	
Bampi BALPEX serie MP	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
Bampi BALPEX Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
BARBI EASYPRESS (Industrial Blansol)	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	Rfz 12		578490
	Rfz 16		578492
	Rfz 20		578494
	Rfz 25		578496
	Rfz 32		578498
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
BARBI MULTIPLEX (Industrial Blansol)	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	Rfz 16		578492
	Rfz 18		578638
	Rfz 20		578494
	Rfz 25		578496
	Rfz 32		578498
	TH 16		578352
	TH 20		578358
TH 26		578362	
TH 32		578364	
TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788	
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	
U 16		578374	
U 18		578376	
U 20		578378	
U 25		578380	
U 32		578382	
U 40		578386	
BEGETUBE/ IVAR	B 14		578466
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
Béné inox Série 41	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
Brass Form Master Press	H 16		578400
	H 18		578404
	H 20		578406
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	U 16		578374
	U 18		578376
U 20		578378	
Brass & Fittings PRESSMAN MultiPress	Rfz 16		578492
	Rfz 18		578638
	Acz 20		578612
	Rfz 25		578496
	Rfz 32		578498
Brass & Fittings PRESSMAN RetiPress	Rfz 16		578492
	Rfz 18		578638
	Acz 20		578612
	Rfz 25		578496
	Rfz 32		578498
BRASSTECH MULTIthermoSAN Brasspress	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
TH 16		578352	
TH 18		578356	
TH 20		578358	
TH 26		578362	
TH 32		578364	
TH 40		578624	
TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788	
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	
U 16		578374	
U 18		578376	
U 20		578378	
C 26		578392	
U 32		578382	

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
C			
Cello Products -B->Press	VUS ½" (OD 15,9 mm)		578566
	VUS ¾" (OD 22,2 mm)		578568
	VUS 1" (OD 28,6 mm)		578570
	VUS 1¼" (OD 34,9 mm)		578606
CGR DYNAFLU multicouche	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 20		578378
	U 32		578382
U 40		578386	
CGR DYNAFLU PER	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	RFz 12		578490
RFz 16		578492	
RFz 20		578494	
RFz 25		578496	
CHIALI CHIALIPEX	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
Climatek Clima Therm	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
Climatrix Climatrix Rhinopex	H 16		578400
	H 20		578406
	U 16		578374
	U 20		578378
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788	
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	
Climatrix Variotherm System TH ClouSet	TH 11,6		578344
	TH 16		578352
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 16		578352
TH 18		578356	
TH 20		578358	
TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788	
Comap PEX Press	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	TH 14		578348
Comap Multiskin	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	THL 32		578368
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	U 32		578382
	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
Comap Multiskin Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	THL 32		578368
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 20		578378
	U 32		578382
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
COMISA Press System	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
H 26		578410	
H 32		578412	
B 14		578466	
B 16		578468	
B 18		578470	
B 20		578472	
B 26		578474	
B 32		578476	
COMISA Press System Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
CONEL CONNECT MULTI	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788	
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	
U 16		578374	
U 20		578378	
(DN 26)		578380	
U 32		578382	
VP 16		578482	
VP 20		578484	
VP 32		578488	
CONEL CONNECT MV2	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Conex Bänninger >B< Flex	F 16		578456
	F 18		578458
	F 20		578460
	F 32		578464
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 32 S (PR-2B)	Mini Z8	574734
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 16		578492
	RFz 18		578638
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 32		578364
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
Conex Bänninger >B< MaxiPro	BMP ¼"		578700
	BMP ⅜"		578702
	BMP ½"		578704
	BMP ⅝"		578706
	BMP ¾"		578708
	BMP 1"		578710
	BMP 1 ¼"		578712
	BMP 1 ½"		578714
Conex Bänninger >B< Press	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 14 S (PR-2B)	Mini Z8	574800
	V 15 S (PR-2B)	Mini Z8	574752
	V 16 S (PR-2B)	Mini Z8	574802
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	
Conex Bänninger >B< Press Carbon	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
Conex Bänninger >B< Press Gas	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 14 S (PR-2B)	Mini Z8	574800
	V 15 S (PR-2B)	Mini Z8	574752
	V 16 S (PR-2B)	Mini Z8	574802
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	
Conex Bänninger >B< Press Inox	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
Conex Bänninger >B< Press Solar	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 14 S (PR-2B)	Mini Z8	574800
	V 15 S (PR-2B)	Mini Z8	574752
	V 16 S (PR-2B)	Mini Z8	574802
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
D			
Debrunner Acifer d-a Presssystem C-Stahl	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
M 35 S (PR-2B)	Mini Z8	574746	
DIWAsystems	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
TH 40		578624	
DUOPIPE Systems DUOFIL MKSYSTEM	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
DW Verbundrohr multitubo systems	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
E			
EBRILLE Isomomflex	U 16		578374
	U 20		578378
	U 25		578380
	H 26		578410
	TH 26		578362
	TH 26 S (PR-2B)	Mini Z8	574794
U 32		578382	
EBRILLE Monflex	U 16		578374
	U 20		578378
	U 25		578380
	H 26		578410
	TH 26		578362
	TH 26 S (PR-2B)	Mini Z8	574794
U 32		578382	
EFFEBI EFFEBI-PRESS Aisi316 System M Profile ¹⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
EFFEBI EFFEBI-PRESS Aisi316 System V Profile	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	
EFFEBI EFFEBI-PRESS Carbon-S System M Profile ¹⁾	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
M 28 S (PR-2B)	Mini Z8	574744	
M 35 S (PR-2B)	Mini Z8	574746	
EFFEBI EFFEBI-PRESS Carbon-S System V Profile	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
EFFEBI EFFEBI-PRESS UNICO	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
	EFFEBI EFFEBI-PRESS UNICO ⁴⁾ (GAS)	V 12	
V 15			578328
V 18			578332
V 22			578334
V 28			578336
V 35			578604
V 12 S (PR-2B)		Mini Z8	574748
V 15 S (PR-2B)		Mini Z8	574752
V 18 S (PR-2B)		Mini Z8	574756
V 22 S (PR-2B)		Mini Z8	574758
V 28 S (PR-2B)		Mini Z8	574760
V 35 S (PR-2B)		Mini Z8	574762
EFFEBI PRESSTIGE		M 15	
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	
EFFEBI PRESSTIGE 4E05	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
EFFEBI PRESSTIGE-GAS ⁴⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	V 15		578328
	V 18		578332
	V 22		578334
V 28		578336	
V 35		578604	
V 15 S (PR-2B)	Mini Z8	574752	
V 18 S (PR-2B)	Mini Z8	574756	
V 22 S (PR-2B)	Mini Z8	574758	
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	
EFFEBI TOF-GAS MULTIPINZA	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	U 32		578382

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
EFFEBI TOF MULTIPINZA	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	F 16		578456
	F 18		578458
	F 20		578460
	F 26		578462
	F 32		578464
	Fz 40		578478
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 18		578376
U 20		578378	
U 25		578380	
C 26		578392	
U 32		578382	
U 40		578386	
B 16		578468	
B 18		578470	
B 20		578472	
B 26		578474	
B 32		578476	
EFIELD MULTILAYER PRESS DINGAS	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
EFIELD MULTILAYER PRESS WATER	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
Elkhart APOLLOXPRESS Fittings Copper and Low-Lead Brass	VUS ½" (OD 15,9 mm)		578566
	VUS ¾" (OD 22,2 mm)		578568
	VUS 1" (OD 28,6 mm)		578570
	VUS 1¼" (OD 34,9 mm)		578606
	ELYDAN izeo	RFz 16	
RFz 20		578494	
RFz 25		578496	
RFz 32		578498	
U 16		578374	
U 20		578378	
U 25		578380	
U 32		578382	
EMMETI GERPEX- FIVPRESS	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	H 16		578400
	H 20		578406
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
U 16		578374	
U 20		578378	
EMPUR	TH 14		578348
	TH 15		578350
	TH 16		578352
	TH 17		578354
	TH 20		578358
TH 25		578360	
TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788	
Esta Rohr simplesta SH M	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacture.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacture.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacture.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Esta Rohr simplesta ST M	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
EUROTUBI	M 12		578310
EUROPA	M 15		578312
C-Steel Pressfitting System M-Profile ¹⁾	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
EUROTUBI	M 15		578312
EUROPA	M 18		578314
Inox Pressfitting System M-Profile ¹⁾	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
M 35 S (PR-2B)	Mini Z8	574746	
Evans Components Presslok	VAU 15 (½")		578630
	VAU 20 (¾")		578632
	VAU 25 (1")		578634
F			
FAR Rubinetterie PRESSFAR	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
U 40		578386	
F.B.Q. BARONIO BQ PRESS SOLAR	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
F.B.Q. BARONIO BQ PRESS WATER	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
F.B.Q. BARONIO BQ PRESS C-STEEL	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
F.B.Q. BARONIO BQ PRESS GAS	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
Fercofloor DUO Press FERCO PEX	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788		
TH 32 S (PR-2B)	Mini Z8	574798		
Fercofloor DUO Press MULTIFER	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788		
TH 32 S (PR-2B)	Mini Z8	574798		
FERRO systems BRASELLI GPF GAS	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 25 S (PR-2B)	Mini Z8	574792	
	TH 32 S (PR-2B)	Mini Z8	574798	
	FERRO systems BRASELLI GPF MULT Pressfitting MULTICAPA	U 16		578374
		U 18		578376
U 20			578378	
U 25			578380	
U 32			578382	
U 40			578386	
FERRO systems BRASELLI GPF PPSU Pressfitting PEX y MULTICAPA		U 16		578374
		U 18		578376
		U 20		578378
		U 25		578380
	U 32		578382	
	U 40		578386	
	FERRO systems BRASELLI GPF PRESS Pressfitting PEX FILINOX Instalpress Steel	RFz 16		578492
		RFz 20		578494
		RFz 25		578496
		RFz 32		578498
M 15			578312	
M 18			578314	
M 22			578316	
M 28			578318	
M 35			578390	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)	Mini Z8	574740		
M 22 S (PR-2B)	Mini Z8	574742		
M 28 S (PR-2B)	Mini Z8	574744		
M 35 S (PR-2B)	Mini Z8	574746		
FILINOX Instalpress Inox	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
Fittings Estándar ECO-PRESS	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
	Fittings Estándar MULTICAPA	RFz 16		578492
		RFz 18		578638
		RFz 20		578494
		RFz 25		578496
		RFz 32		578498

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	
Fittings Estándar PE-X	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
FORNARA ForPress	B 16		578468	
	B 20		578472	
	B 26		578474	
	B 32		578476	
	F 16		578456	
	F 20		578460	
	F 26		578462	
	F 32		578464	
	F 16 S (PR-2B)	Mini Z8	574728	
	F 20 S (PR-2B)	Mini Z8	574730	
	F 26 S (PR-2B)	Mini Z8	574732	
	F 32 S (PR-2B)	Mini Z8	574734	
	H 16		578400	
	H 20		578406	
	H 26		578410	
	H 32		578412	
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	U 16		578374	
	U 20		578378	
	C 26		578392	
	U 32		578382	
	FORZA	K16/P18		578592
	WATER CRIMP (AUS)	K/20		578594
		K/25		578596
		K32		578598
	K1/40		578600	
FORZA STAINLESS WATER CRIMP	K16/P18		578592	
	K/20		578594	
FORZA	U 16		578374	
STESSO PEX	U 20		578378	
WATER AND GAS CRIMP AUS)	U 25		578380	
	U 32		578382	
	U 40		578386	
FORZA	K16/P18		578592	
GAS CRIMP (AUS)	K/20		578594	
	K/25		578596	
	K32		578598	
	K1/40		578600	
FORZA	VAU 15 (OD 12,7 mm)		578630	
COPPER V PRESS (AUS)	VAU 20 (OD 19,1 mm)		578632	
	VAU 25 (OD 25,4 mm)		578634	
	VAU 32 (OD 31,8 mm)		578636	
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804	
	VAU 20 S (PR-2B) (OD 19,1 mm)	Mini Z8	574806	
	VAU 25 S (PR-2B) (OD 25,4 mm)	Mini Z8	574808	
FORZA	V 15		578328	
STAINLESS V PRESS (AUS)	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	FRABO	M 15		578312
	FRABOPRESS 316 GAS M	M 18		578314
M 22			578316	
M 28			578318	
M 35			578390	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	
FRABO	V 15		578328	
FRABOPRESS 316 GAS V	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
FRABO	M 15		578312	
FRABOPRESS 316 M	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
		M 35 S (PR-2B)	Mini Z8	574746
	FRABO	V 12		578324
FRABOPRESS 316 V	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
FRABO	V 12		578324	
FRABOPRESS CHROME	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
FRABO	M 15		578312	
FRABOPRESS C-STEEL M	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
		M 35 S (PR-2B)	Mini Z8	574746
	FRABO	V 12		578324
FRABOPRESS C-STEEL V	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
FRABO	M 12		578310	
FRABOPRESS GAS M	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 12 S (PR-2B)	Mini Z8	574736	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
		M 35 S (PR-2B)	Mini Z8	574746

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
FRABO FRABOPRESS GAS V	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
FRABO FRABOPRESS KOMBI	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
FRABO FRABOPRESS M	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
FRABO FRABOPRESS SOLAR	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
FRABO FRABOPRESS V	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
Fränkische alpelx-duo XS	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	TH 16		578352
	TH 20		578358
Fränkische alpelx F50 PROFIL	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	H 16		578400
	H 20		578406
(DN 26)	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
Fränkische alpelx L	Fz 40		578478

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
G			
gabotherm H+S	TH 10		578342
	TH 12		578346
	TH 14		578348
	TH 15		578350
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
Gallagher USA YogaPipe ACR	H 12 (1/4")		578396
	U 14 (3/8")		578372
	U 16 (1/2")		578374
	U 18 (5/8")		578376
	U 20 (3/4")		578378
	U 25 (7/8")		578380
Geberit Mapress C-STAHL	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
Geberit Mapress Edelstahl	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
Geberit Mapress Edelstahl Gas	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
Geberit Mapress Kupfer	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
Geberit Mapress Kupfer Gas	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
Geberit Mepla	G 16		578444
	G 20		578446
	G 26		578448
	G 32		578450
	G 40		578452
	G 26		578448
Geberit Mepla Therm	G 20		578446
	G 26		578448
Geberit Volex	TH 16		578352
	TH 20		578358
	TH 26		578362

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
General Fittings 5T00	H 16		578400	General Fittings Trident Gas	H 16		578400
	H 20		578406		H 20		578406
	H 26		578410		H 26		578410
	H 32		578412		H 32		578412
	TH 16		578352		TH 16		578352
	TH 20		578358		TH 20		578358
	TH 26		578362		TH 26		578362
	TH 32		578364		TH 32		578364
	TH 40		578624		TH 16 S (PR-2B)		574782
	TH 16 S (PR-2B)	Mini Z8	574782		TH 20 S (PR-2B)	Mini Z8	574788
	TH 20 S (PR-2B)	Mini Z8	574788		TH 26 S (PR-2B)	Mini Z8	574794
	TH 26 S (PR-2B)	Mini Z8	574794		TH 32 S (PR-2B)	Mini Z8	574798
	TH 32 S (PR-2B)	Mini Z8	574798		U 16		578374
	U 16		578374		U 20		578378
	U 20		578378		U 32		578382
	U 32		578382		U 40		578386
U 40		578386	Giacomini	H 16		578400	
General Fittings Ewoprex	H 16		578400	Raccordi RM	H 20		578406
	H 20		578406	Giacomini	H 26		578410
	H 26		578410	H 32		578412	
	H 32		578412	TH 16		578352	
	TH 16		578352	TH 20		578358	
	TH 20		578358	TH 26		578362	
	TH 26		578362	TH 32		578364	
	TH 32		578364	TH 40		578624	
	TH 40		578624	U 16		578374	
	TH 16 S (PR-2B)	Mini Z8	574782	U 20		578378	
	TH 20 S (PR-2B)	Mini Z8	574788	U 32		578382	
	TH 26 S (PR-2B)	Mini Z8	574794	U 40		578386	
	TH 32 S (PR-2B)	Mini Z8	574798	Giacomini	H 16		578400
	U 16		578374	RM MULTIGAS	H 20		578406
	U 20		578378	H 26		578410	
	U 32		578382	H 32		578412	
U 40		578386	TH 16		578352		
General Fittings Serie 5S00	B 16		578468	TH 20		578358	
	B 18		578470	TH 26		578362	
	B 20		578472	TH 32		578364	
	B 26		578474	U 16		578374	
	B 32		578476	U 20		578378	
	F 16		578456	U 32		578382	
	F 20		578460	U 40		578386	
	F 26		578462	Giacomini	V 15		578328
	F 32		578464	Valvole Giacomini	V 18		578332
	F 16 S (PR-2B)	Mini Z8	574728	serie R850V	V 22		578334
	F 20 S (PR-2B)	Mini Z8	574730	V 28		578336	
	F 24 S (PR-2B)	Mini Z8	574732	V 35		578604	
	F 32 S (PR-2B)	Mini Z8	574734	V 15 S (PR-2B)	Mini Z8	574752	
	H 16		578400	V 18 S (PR-2B)	Mini Z8	574756	
	H 18		578404	V 22 S (PR-2B)	Mini Z8	574758	
	H 20		578406	V 28 S (PR-2B)	Mini Z8	574760	
	H 25		578408	V 35 S (PR-2B)	Mini Z8	574762	
	H 26		578410	SA 15		578514	
	H 32		578412	SA 18		578518	
	TH 16		578352	SA 22		578520	
	TH 18		578356	SA 28		578522	
	TH 20		578358	M 15		578312	
	TH 25		578360	M 18		578314	
	TH 26		578362	M 22		578316	
	TH 32		578364	M 28		578318	
	TH 40		578624	M 35		578390	
	TH 16 S (PR-2B)	Mini Z8	574782	M 15 S (PR-2B)	Mini Z8	574738	
	TH 20 S (PR-2B)	Mini Z8	574788	M 18 S (PR-2B)	Mini Z8	574740	
	TH 26 S (PR-2B)	Mini Z8	574794	M 22 S (PR-2B)	Mini Z8	574742	
	TH 32 S (PR-2B)	Mini Z8	574798	M 28 S (PR-2B)	Mini Z8	574744	
	U 16		578374	M 35 S (PR-2B)	Mini Z8	574746	
	U 18		578376	Gotan Pipe	U 16		578374
	U 20		578378	Systems	U 20		578378
U 25		578380	(Scandinavia)	U 25		578380	
U 32		578382	Alu-Pres	U 32		578382	
U 40		578386	U 40		578386		
General Fittings Trident	B 16		578468	Grinnell G-PRESS	VUS ½" (OD 15,9 mm)		578566
	F 16		578456	Copper Fittings	VUS ¾" (OD 22,2 mm)		578568
	F 16 S (PR-2B)	Mini Z8	574728	VUS 1" (OD 28,6 mm)		578570	
	H 16		578400	VUS 1¼" (OD 34,9 mm)		578606	
	H 20		578406	GS	TH 14		578348
	H 26		578410	Wärmesysteme	TH 16		578352
	H 32		578412	System TH	TH 20		578358
	TH 16		578352	TH 26		578362	
	TH 20		578358	TH 32		578364	
	TH 26		578362	TH 40		578624	
	TH 32		578364	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 16 S (PR-2B)	Mini Z8	574782	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 20 S (PR-2B)	Mini Z8	574788	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 26 S (PR-2B)	Mini Z8	574794	TH 32 S (PR-2B)	Mini Z8	574798	
	TH 32 S (PR-2B)	Mini Z8	574798				
	U 16		578374				
U 20		578378					
U 32		578382					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For taking suitable pressing inserts.
- Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
GS Wärmesysteme System V	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
H				
HakaGerodur HAKASAN	TH 10		578342	
	TH 11,6		578344	
	TH 12		578346	
	TH 14		578348	
	TH 16		578352	
	TH 17		578354	
	TH 18		578356	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	HASTINIK Hastinik/Hitpress	M 15		578312
		M 18		578314
M 22			578316	
M 28			578318	
M 35			578390	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	
heima24	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	U 16		578374	
	U 20		578378	
	U 25		578380	
U 32		578382		
HELIROMA Klimapress	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
HELIROMA Romapress	Rfz 16		578492	
	Rfz 20		578494	
	Rfz 25		578496	
	Rfz 32		578498	
Henco	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 26		578362	
	HE 32		578370	
Herotec tempusPRESS PLUS	H 16		578400	
	H 20		578406	
	H 25		578408	
	H 32		578412	
	Rfz 16		578492	
	Rfz 20		578494	
	Rfz 25		578496	
	Rfz 32		578498	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
	TH 40		578624	
TH 16 S (PR-2B)	Mini Z8	574782		
TH 20 S (PR-2B)	Mini Z8	574788		
TH 32 S (PR-2B)	Mini Z8	574798		
U 16		578374		
U 20		578378		
U 25		578380		
U 32		578382		
U 40		578386		
Herotec tempusPRESS PLUS PPSU	H 16		578400	
	H 20		578406	
	H 25		578408	
	H 32		578412	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 32 S (PR-2B)	Mini Z8	574798	
	U 16		578374	
U 20		578378		
U 25		578380		
U 32		578382		
U 40		578386		

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
HERZ PIPEFIX	TH 10		578342	
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	HIDRONIX MULTIGAS	TH 16		578352
		TH 20		578358
TH 26			578362	
HIDRONIX MULTIPIPE	TH 14		578348	
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	H 14		578398	
	H 16		578400	
	H 18		578404	
	H 20		578406	
	H 26		578410	
	H 32		578412	
	U 14		578372	
	U 16		578374	
	U 18		578376	
	U 20		578378	
	C 26		578392	
	U 32		578382	
	HIDRONIX UNICO	TH 14		578348
TH 16			578352	
TH 20			578358	
TH 26			578362	
TH 32			578364	
H 14			578398	
H 16			578400	
H 18			578404	
H 20			578406	
H 26			578410	
H 32			578412	
U 14			578372	
U 16		578374		
U 18		578376		
U 20		578378		
C 26		578392		
U 32		578382		
HITEC Sistema Multistrato	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	HITHERM-ISOTUBI NUMEPRESS	M 15		578312
M 18			578314	
M 22			578316	
M 28			578318	
M 35			578390	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	
HITHERM-ISOTUBI HTpress	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
HITHERM-ISOTUBI HTfire	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
HITHERM-ISOTUBI HTair	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
Hopewell press fit system	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
hp praski BAVARIA-press	TH 10		578342
	TH 12		578346
	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	ICMA Sempiter	H 16	
H 20			578406
H 25			578408
H 26			578410
H 32			578412
TH 16			578352
TH 20			578358
TH 25			578360
TH 26			578362
TH 32			578364
TH 40			578624
TH 16 S (PR-2B)		Mini Z8	574782
TH 20 S (PR-2B)		Mini Z8	574788
TH 26 S (PR-2B)		Mini Z8	574794
TH 32 S (PR-2B)		Mini Z8	574798
U 16			578374
U 20			578378
U 25			578380
C 26			578392
U 32			578382
U 40			578386
ICMA Sempigas		TH 16	
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	
Idrosanitaria Bonomi Homegas	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
TH 26 S (PR-2B)	Mini Z8	574794	
Idrosanitaria Bonomi Idropress	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
IDROSISTEMI Ta-Press	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	Fz 40		578478
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
	U 40		578386
	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.
IDROTRADE Storm Multipinza	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	THL 32		578368
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
U 20		578378	
IDROTRADE StormPRES ¹⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
IDROTRADE StormSTEEL ¹⁾	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
ILTA INOX/CHIBRO Pressfitting Cuni	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
ILTA INOX/CHIBRO Pressfitting inox	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
Instantor Copper Press Imperial	VI ½" (OD 14,7 mm)		578716
	VI ¾" (OD 21,0 mm)		578718
	VI 1" (OD 27,4 mm)		578720
Instantor Copper Press Metric	M 15		578312
	M 22		578316
	M 28		578318
	M 15 S (PR-2B)	Mini Z8	574738
	M 22 S (PR-2B)	Mini Z8	574742
Instantor Press System	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
IPA IPANA Press	TH 10		578342
	TH 11,6		578344
	TH 12		578346
	TH 14		578348
	TH 15		578350
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 22		578588
	TH 25		578360
	TH 26		578362
	TH 28		578590
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
IPA Thu	TH 16		578352
IPANA Press	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
IPALPEX (Industrie du Plastique et Accessoires)	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	THL 32		578368
	TH 40		578624
IPLEX PIPELINES AUSTRALIA Iplex Pro-fit	K16/P18		578592
IPLEX PIPELINES AUSTRALIA Iplex K1 (Gas)	K16/P18		578592
	K/20		578594
	K/25		578596
	K32		578598
	K1/40		578600
IPLEX PIPELINES AUSTRALIA Iplex K2	K16/P18		578592
	K/20		578594
	K/25		578596
ISOTUBI NUMEPRESS	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578320
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
IVAR ALPEX-GAS	B 20		578472
	B 26		578474
	B 32		578476
IVAR MULTI PRESS GAS ITALIA	TH 16		578352
	TH 20		578358
	TH 26		578362
	H 16		578400
	H 20		578406
	H 26		578410
	U 16		578374
	U 20		578378
IVAR Multi Press MP	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	F 16		578456
	F 18		578458
	F 20		578460
	F 26		578462
	F 32		578464
	Fz 40		578478
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	C 26		578392
	U 32		578382
	U 40		578386
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
IVAR Multi Press Leak (MPL)	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
		TH 32		578364
		TH 16 S (PR-2B)	Mini Z8	574782
		TH 20 S (PR-2B)	Mini Z8	574788
		TH 26 S (PR-2B)	Mini Z8	574794
		TH 32 S (PR-2B)	Mini Z8	574798
		F 16		578456
		F 20		578460
		F 26		578462
		F 32		578464
		F 16 S (PR-2B)	Mini Z8	574728
		F 20 S (PR-2B)	Mini Z8	574730
		F 26 S (PR-2B)	Mini Z8	574732
		F 32 S (PR-2B)	Mini Z8	574734
		H 16		578400
		H 20		578406
		H 26		578410
		H 32		578412
		U 16		578374
		U 20		578378
		U 25		578380
		C 26		578392
		U 32		578382
		B 16		578468
		B 20		578472
		B 26		578474
		B 32		578476
	IVAR Plastic Multi Press PMP	TH 16		578352
		TH 20		578358
		TH 25		578360
			TH 26	
		TH 32		578364
		TH 16 S (PR-2B)	Mini Z8	574782
		TH 20 S (PR-2B)	Mini Z8	574788
		TH 26 S (PR-2B)	Mini Z8	574794
		TH 32 S (PR-2B)	Mini Z8	574798
		F 16		578456
		F 20		578460
		F 26		578462
		F 32		578464
		F 16 S (PR-2B)	Mini Z8	574728
		F 20 S (PR-2B)	Mini Z8	574730
		F 26 S (PR-2B)	Mini Z8	574732
		F 32 S (PR-2B)	Mini Z8	574734
		H 16		578400
		H 20		578406
		H 26		578410
		H 32		578412
		U 16		578374
		U 20		578378
		U 25		578380
		C 26		578392
		U 32		578382
		B 16		578468
		B 20		578472
		B 26		578474
		B 32		578476
IVAR Plastic Multi Press Leak (PMPL)		TH 16		578352
		TH 20		578358
		TH 26		578362
		TH 32		578364
		TH 16 S (PR-2B)	Mini Z8	574782
		TH 20 S (PR-2B)	Mini Z8	574788
		TH 26 S (PR-2B)	Mini Z8	574794
		TH 32 S (PR-2B)	Mini Z8	574798
		F 16		578456
		F 20		578460
		F 26		578462
		F 32		578464
		F 16 S (PR-2B)	Mini Z8	574728
		F 20 S (PR-2B)	Mini Z8	574730
		F 26 S (PR-2B)	Mini Z8	574732
		F 32 S (PR-2B)	Mini Z8	574734
		H 16		578400
		H 20		578406
		H 26		578410
		H 32		578412
		U 16		578374
		U 20		578378
		C 26		578392
		U 32		578382
		B 16		578468
		B 20		578472
		B 26		578474
		B 32		578476
	IVT Edelstahl-Presssystem	M 15		578312
		M 18		578314
		M 22		578316
		M 28		578318
		M 35		578320
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	
IVT PRIPRESS	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
J				
Jäger - Aquatec Aquapress H	H 14		578398	
	H 16		578400	
	H 17		578402	
	H 18		578404	
	H 20		578406	
	H 26		578410	
	H 32		578412	
Jäger - Aquatec C-Stahl Press Typ M	U 40		578386	
	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
Jäger - Aquatec Edelstahl Press Typ M	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
	Jäger - Aquatec Kupfer Press Typ V	V 15		578328
V 18			578332	
V 22			578334	
V 28			578336	
V 35			578404	
V 15 S (PR-2B)		Mini Z8	574752	
V 18 S (PR-2B)		Mini Z8	574756	
V 22 S (PR-2B)		Mini Z8	574758	
V 28 S (PR-2B)		Mini Z8	574760	
V 35 S (PR-2B)		Mini Z8	574762	
Jansen AG JANSEN COMISA		TH 14		578348
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	Jaraflex- Presssystem	TH 14		578348
TH 16			578352	
TH 17			578354	
TH 18			578356	
TH 20			578358	
TH 25			578360	
TH 26			578362	
TH 32			578364	
TH 40			578624	
TH 16 S (PR-2B)		Mini Z8	574782	
TH 20 S (PR-2B)		Mini Z8	574788	
TH 26 S (PR-2B)		Mini Z8	574794	
TH 32 S (PR-2B)		Mini Z8	574798	
JUNGWOO JWPress		VUS ½" (OD 15,9 mm)		578566
		VUS ¾" (OD 22,2 mm)		578568
	VUS 1" (OD 28,6 mm)		578570	
	VUS 1¼" (OD 34,9 mm)		578606	
K				
KAN KAN-therm Press	U 16		578374	
	U 20		578378	
	U 25		578380	
	C 26		578392	
	U 32		578382	
	U 40		578386	

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	
KAN KAN-therm Press LBP	TH 14		578348	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	U 14		578372	
	U 16		578374	
	U 20		578378	
	U 25		578380	
	C 26		578392	
	U 32		578382	
	U 40		578386	
	KAN KAN-therm Inox	M 12		578310
		M 15		578312
		M 18 ¹⁾		578314
M 22			578316	
M 28 ¹⁾			578318	
M 35			578390	
M 12 S (PR-2B)		Mini Z8	574736	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
KAN KAN-therm Steel	M 35 S (PR-2B)	Mini Z8	574746	
	M 12		578310	
	M 15		578312	
	M 18 ¹⁾		578314	
	M 22		578316	
	M 28 ¹⁾		578318	
	M 35		578390	
	M 12 S (PR-2B)	Mini Z8	574736	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
KAN KAN-therm UltraPRESS	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
	TH 14		578348	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	U 14		578372	
	U 16		578374	
	U 20		578378	
	U 25		578380	
	C 26		578392	
	U 32		578382	
	U 40		578386	
	KE KELIT COPPERFIX Kupfer	M 15		578312
M 18			578314	
M 22			578316	
M 28			578318	
M 35			578390	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
KE KELIT KELOX	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
KE KELIT KELOX-PPSU-W	U 32		578382	
	U 40		578386	
	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
KE KELIT KELOX-ULTRAX	U 40		578386	
	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
	U 40		578386	
KE KELIT KELOX-ULTRAX-W	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
	U 40		578386	

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
KE KELIT KELO-WINDOW-U	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
KE KELIT KELOX-WINDOW-W	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
KE KELIT steelFIX C-Stahl	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	KE KELIT steelFIX Edelstahl	M 15	
M 18			578314
M 22			578316
M 28			578318
M 35			578390
M 15 S (PR-2B)		Mini Z8	574738
M 18 S (PR-2B)		Mini Z8	574740
M 22 S (PR-2B)		Mini Z8	574742
M 28 S (PR-2B)		Mini Z8	574744
M 35 S (PR-2B)		Mini Z8	574746
KEMBLA KemPress (AUS)		VAU 15 (OD 12,7 mm)	
	VAU 20 (OD 19,1 mm)		578632
	VAU 25 (OD 25,4 mm)		578634
	VAU 32 (OD 31,8 mm)		578636
KEMBLA KemPress Gas (AUS)	VAU 15 (OD 12,7 mm)		578630
	VAU 20 (OD 19,1 mm)		578632
	VAU 25 (OD 25,4 mm)		578634
	VAU 32 (OD 31,8 mm)		578636
KISAN Kisan KD	KI 16		578524
	KI 20		578526
	KI 25		578528
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	KISAN Kisan WL	KI 16	
KI 20			578526
KI 25			578528
KI 32			578530
TH 16			578352
TH 20			578358
TH 25			578360
TH 32			578364
TH 16 S (PR-2B)		Mini Z8	574782
TH 20 S (PR-2B)	Mini Z8	574788	
TH 32 S (PR-2B)	Mini Z8	574798	
KISAN Kisan WM	KI 16		578524
	KI 20		578526
	KI 25		578528
	KI 32		578530
KISAN Kisan WR	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	TH 20		578358
	TH 25		578360
	TH 32		578364
	TH 40		578624
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 32 S (PR-2B)	Mini Z8	574798
KISAN Kistal C	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
KISAN Kistal Inox	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746

L

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
LK Systems LK >B-Press	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	LK Systems LK >B-Press Eltörzinkat	V 12		578324
		V 15		578328
V 18			578332	
V 22			578334	
V 28			578336	
V 35			578604	
V 12 S (PR-2B)		Mini Z8	574748	
V 15 S (PR-2B)		Mini Z8	574752	
V 18 S (PR-2B)		Mini Z8	574756	
V 22 S (PR-2B)		Mini Z8	574758	
LK Systems LK >B-Press Gas	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
LK Systems LK Universal	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
	TH 40		578624	
LVI-DAHL Altech-Alupez	U 16		578374	
	U 20		578378	
	U 25		578380	
MAINCOR MAINPRESS	U 16		578374	
	U 20		578378	
	U 25		578380	
	U 32		578382	
MAINCOR MAINFLOR	U 16		578374	
	U 20		578378	
Mair Heizechnik M-Press	H 11,5		578394	
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
Ma.s.ter System PRESSMASTER	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
Meier Tobler Metalplast - Stramax Serie MM	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 32 S (PR-2B)	Mini Z8	574798	
	H 14		578398	
	H 16		578400	
	H 18		578404	
H 20		578406		
H 26		578410		
H 32		578412		
U 14		578372		
U 16		578374		
U 18		578376		
U 20		578378		
U 25		578380		
U 32		578382		
U 40		578386		
METALGRUP Permatubo	H 16		578400	
	H 20		578406	
	H 25		578408	
	H 32		578412	
	RfZ 16		578492	
	RfZ 20		578494	
	RfZ 25		578496	
	RfZ 32		578498	
	TH 16		578352	
	TH 20		578358	
TH 25		578360		
TH 32		578364		
TH 40		578624		
TH 16 S (PR-2B)	Mini Z8	574782		
TH 20 S (PR-2B)	Mini Z8	574788		
TH 32 S (PR-2B)	Mini Z8	574798		
U 16		578374		
U 20		578378		
U 25		578380		
U 32		578382		
U 40		578386		

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
METALGRUP PexGrup	RFz 16		578492	NIBCO (USA) Press System Copper	VUS ½" (OD 15,9 mm)		578566
	RFz 20		578494		VUS ¾" (OD 22,2 mm)		578568
	RFz 25		578496		VUS 1" (OD 28,6 mm)		578570
	RFz 32		578498		VUS 1¼" (OD 34,9 mm)		578606
METALGRUP MultiGrup	U 16		578374	NICOLL FLUXO	TH 16		578352
	U 18		578376		TH 20		578358
	U 20		578378		TH 25		578360
	U 25		578380		TH 26		578362
	U 32		578382		TH 32		578364
Mueller Industries Streamline PRS	VUS ½" (OD 15,9 mm)		578566		TH 40		578624
	VUS ¾" (OD 22,2 mm)		578568		TH 16 S (PR-2B)	Mini Z8	574782
	VUS 1" (OD 28,6 mm)		578570		TH 20 S (PR-2B)	Mini Z8	574788
	VUS 1¼" (OD 34,9 mm)		578606		TH 26 S (PR-2B)	Mini Z8	574794
MULTITHERM PRESSSYSTEM	TH 16		578352		TH 32 S (PR-2B)	Mini Z8	574798
	TH 20		578358	NUPI Industrie Italiane Multinupi	B 16		578468
	TH 26		578362		B 18		578470
	TH 32		578364		B 20		578472
	TH 40		578624		B 26		578474
	TH 16 S (PR-2B)	Mini Z8	574782		B 32		578476
	TH 20 S (PR-2B)	Mini Z8	574788		F 16		578456
	TH 26 S (PR-2B)	Mini Z8	574794		F 18		578458
TH 32 S (PR-2B)	Mini Z8	574798	F 20			578460	
Multicap Industrial AIS PEX	RFz 16		578492	F 26		578462	
	RFz 20		578494	F 32		578464	
	RFz 25		578496	F 16 S (PR-2B)	Mini Z8	574728	
	RFz 32		578498	F 20 S (PR-2B)	Mini Z8	574730	
	U 16		578374	F 26 S (PR-2B)	Mini Z8	574732	
Multicap Industrial AIS XPRT	U 20		578378	F 32 S (PR-2B)	Mini Z8	574734	
	U 25		578380	H 16		578400	
	U 32		578382	H 18		578404	
	H 16		578400	H 20		578406	
	H 20		578406	H 25		578408	
	H 25		578408	H 26		578410	
	H 26		578410	H 32		578412	
	H 32		578412	TH 16		578352	
	RFz 16		578492	TH 18		578356	
	RFz 20		578494	TH 20		578358	
	RFz 25		578496	TH 25		578360	
	RFz 32		578498	TH 26		578362	
	TH 16		578352	TH 32		578364	
	TH 20		578358	TH 40		578624	
	TH 25		578360	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 26		578362	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 32		578364	TH 26 S (PR-2B)	Mini Z8	574794	
	TH 40		578624	TH 32 S (PR-2B)	Mini Z8	574798	
	U 16		578374	U 14		578372	
	U 20		578378	U 16		578374	
	U 25		578380	U 18		578376	
	U 32		578382	U 20		578378	
	U 40		578386	U 25		578380	
	Multicap Industrial multitubo systems MC	U 16		578374	C 26		578392
		U 18		578376	U 32		578382
U 20			578378	U 40		578386	
U 25			578380	Nussbaum Optifitt-Press	VMP ¾" (OD 17,2 mm)		578660
U 32			578382	Nussbaum Optiflex-Flowpress	VMP ½" (OD 21,3 mm)		578662
Multicap Industrial multitubo systems MM	U 40		578386	VRX 16		578640	
	H 16		578400	VRX 20		578642	
	H 20		578406	VRX 25		578644	
	H 25		578408	VRX 32		578646	
	H 26		578410	Nussbaum Optipress	V 15		578328
	H 32		578412	Aquaplus	V 18		578332
	RFz 16		578492	V 22		578334	
	RFz 20		578494	V 28		578336	
	RFz 25		578496	V 35		578604	
	RFz 32		578498	V 15 S (PR-2B)	Mini Z8	574752	
	TH 16		578352	V 18 S (PR-2B)	Mini Z8	574756	
	TH 20		578358	V 22 S (PR-2B)	Mini Z8	574758	
	TH 25		578360	V 28 S (PR-2B)	Mini Z8	574760	
	TH 26		578362	V 35 S (PR-2B)	Mini Z8	574762	
	TH 32		578364	Nussbaum Optipress Gaz	V 15		578328
	TH 40		578624	V 18		578332	
	TH 16 S (PR-2B)	Mini Z8	574782	V 22		578334	
	TH 20 S (PR-2B)	Mini Z8	574788	V 28		578336	
	TH 26 S (PR-2B)	Mini Z8	574794	V 35		578604	
	TH 32 S (PR-2B)	Mini Z8	574798	V 15 S (PR-2B)	Mini Z8	574752	
	U 16		578374	V 18 S (PR-2B)	Mini Z8	574756	
	U 20		578378	V 22 S (PR-2B)	Mini Z8	574758	
	U 25		578380	V 28 S (PR-2B)	Mini Z8	574760	
	U 32		578382	V 35 S (PR-2B)	Mini Z8	574762	
	U 40		578386	Nussbaum Optipress-Therm	V 15		578328
NEUTHERM MEKUPRESS-HT	H 16		578400	V 18		578332	
	H 20		578406	V 22		578334	
	H 26		578410	V 28		578336	
	H 32		578412	V 35		578604	
				V 15 S (PR-2B)	Mini Z8	574752	
				V 18 S (PR-2B)	Mini Z8	574756	
				V 22 S (PR-2B)	Mini Z8	574758	
				V 28 S (PR-2B)	Mini Z8	574760	
				V 35 S (PR-2B)	Mini Z8	574762	

N

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For taking suitable pressing inserts.
- Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
O			
Oventrop Cofit P	H 16 A H 20 A H 26 A H 32 A		578420 578426 578430 578432
Oventrop Cofit PD	H 16 A H 20 A H 26 A		578420 578426 578430
Oventrop Cofit PDK	H 16 A H 20 A		578420 578426
Oventrop Cofit PD-HT	H 16 A H 20 A H 32 A		578420 578426 578432
Oventrop Cofit PDK-HT	H 16 A H 20 A		578420 578426
P			
PBTub SERTIPRESS	Rfz 12 Rfz 16 Rfz 20 Rfz 25		578490 578492 578494 578496
PBTub SERTI-STEEL ¹⁾	M 15 M 18 M 22 M 28 M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B)		578312 578314 578316 578318 574738 574740 574742 574744
Pegler Yorkshire XPress Carbon	M 12 M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 12 S (PR-2B) M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)		578310 578312 578314 578316 578318 578390 574736 574738 574740 574742 574744 574746
Pegler Yorkshire XPress Copper	M 12 M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 12 S (PR-2B) M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)		578310 578312 578314 578316 578318 578390 574736 574738 574740 574742 574744 574746
Pegler Yorkshire XPress Copper Gas	M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35		578312 578314 578316 578318 578390
Pegler Yorkshire XPress Stainless	M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)		578312 578314 578316 578318 578390 574738 574740 574742 574744 574746
Pegler Yorkshire XPress Stainless Gas	M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35		578312 578314 578316 578318 578390
PERFEXIM PERFEKT SYSTEM	U 16 U 20 U 25 U 32		578374 578378 578380 578382
PERFILTUBO PERFILALUPEX	U 16 U 18 U 20 U 25 U 32 U 40		578374 578376 578378 578380 578382 578386
PERFILTUBO PERFILPRESS	M 15 M 18 M 22 M 28 M 35 M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)		578312 578314 578316 578318 578390 574738 574740 574742 574744 574746
PEXTUBE PexTube	Rfz 16 Rfz 20 Rfz 25 Rfz 32		578492 578494 578496 578498

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Pipelife C-PRESS	M 15 M 18 M 22 M 28 M 35 M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)		578312 578314 578316 578318 578390 574738 574740 574742 574744 574746
Pipelife RADOPRESS	TH 16 TH 18 TH 20 TH 26 TH 32 TH 40 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B) TH 32 S (PR-2B)		578352 578356 578358 578362 578364 578624 574782 574788 574794 574798
Pipetec Connect	TH 16 TH 20 TH 26 TH 32 TH 40 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B) TH 32 S (PR-2B) U 16 U 20 U 25 U 32		578352 578358 578362 578364 578624 574782 574788 574794 574798 578374 578378 578380 578382
PLASTICA ALFA Multypex	TH 16 TH 20 TH 26 TH 32 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B) TH 32 S (PR-2B)		578352 578358 578362 578364 574782 574788 574794 574798
PLASTICA ALFA Multypex Air	TH 16 TH 20 TH 26 TH 32 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B) TH 32 S (PR-2B)		578352 578358 578362 578364 574782 574788 574794 574798
PLASTICA ALFA Multypex alfa Gas	TH 16 TH 20 TH 26 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B)		578352 578358 578362 574782 574788 574794
PLASTICA ALFA Multypex alfa Gas protek	TH 16 TH 20 TH 26 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B)		578352 578358 578362 574782 574788 574794
PLASTICA ALFA Multypex Plus	TH 16 TH 20 TH 26 TH 32 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B) TH 32 S (PR-2B)		578352 578358 578362 578364 574782 574788 574794 574798
PLASTICA ALFA Multypex Thermo	TH 16 TH 20 TH 26 TH 32 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B) TH 32 S (PR-2B)		578352 578358 578362 578364 574782 574788 574794 574798
PLASTICA ALFA Multypex Thermo Plus	TH 16 TH 20 TH 26 TH 32 TH 16 S (PR-2B) TH 20 S (PR-2B) TH 26 S (PR-2B) TH 32 S (PR-2B)		578352 578358 578362 578364 574782 574788 574794 574798
PLÁSTICOS FERRO FERROPLAST GPF MULT Pressfitting MULTICAPA	U 16 U 20 U 25 U 32		578374 578378 578380 578382
PLÁSTICOS FERRO FERROPLAST GPF PPSU Pressfitting PEX y MULTICAPA	U 16 U 20 U 25 U 32		578374 578378 578380 578382
PLÁSTICOS FERRO FERROPLAST GPF PRESS Pressfitting PEX	Rfz 16 Rfz 20 Rfz 25 Rfz 32		578492 578494 578496 578498

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
PLUMBING PLUS EZIPEX Crimp (AUS)	K14/P18		578592
	K/20		578594
	K/25		578596
	K32		578598
	K1/40		578600
PLUMBING PLUS EZIPEX Gas (AUS)	K16/P18		578592
	K/20		578594
	K/25		578596
	K32		578598
	K1/40		578600
PLUMBING PLUS UNIPEX Water & Gas (AUS)	Yz 16 UNI		578740
	Yz 20 UNI		578742
	Yz 25 UNI		578744
	Yz 32 UNI		578746
PLUMBING PLUS EZIPRESS Gas (AUS)	VAU 15 (OD 12,7 mm)		578630
	VAU 20 (OD 19,1 mm)		578632
	VAU 25 (OD 25,4 mm)		578634
	VAU 32 (OD 31,8 mm)		578636
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804
	VAU 20 S (PR-2B) (OD 19,1 mm)	Mini Z8	574806
PLUMBING PLUS EZIPRESS Solar (AUS)	VAU 25 S (PR-2B) (OD 25,4 mm)	Mini Z8	574808
	VAU 15 (OD 12,7 mm)		578630
	VAU 20 (OD 19,1 mm)		578632
	VAU 25 (OD 25,4 mm)		578634
PLUMBING PLUS EZIPRESS Water (AUS)	VAU 32 (OD 31,8 mm)		578636
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804
	VAU 20 S (PR-2B) (OD 19,1 mm)	Mini Z8	574806
	VAU 25 S (PR-2B) (OD 25,4 mm)	Mini Z8	574808
	TH 10		578342
	TH 15		578350
POLYPIPE POLYSURE	TH 22		578588
	TH 28		578590
	M 15		578312
	M 18		578314
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
POLYSAN- C Stahl-Press- System M	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
POLYSAN- Edelstahl Press-System 1.4520	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 35 S (PR-2B)	Mini Z8	574746
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
POLYSAN- Edelstahl Press-System Gas	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	M 15		578312
	M 18		578314
	M 22		578316
POLYSAN- Edelstahl Press-System Wasser	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
POLYSAN- Press-System	TH 26		578362
	TH 32		578364
	TH 40		578424
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	TH 14		578348	
	TH 16		578352	
	TH 17		578354	
	TH 18		578356	
	TH 20		578358	
	POLYSAN-Henco- Press-System	TH 26		578362
		HE 32		578370
		HEz 40 ³⁾		578572
		TH 16 S (PR-2B)	Mini Z8	574782
		TH 20 S (PR-2B)	Mini Z8	574788
		TH 26 S (PR-2B)	Mini Z8	574794
		U 16		578374
	POLYSAN (España) „Rainbow“	U 18		578376
U 20			578378	
U 25			578380	
U 32			578382	
Prandelli Multyrama Pf	U 40		578386	
	H 14		578398	
	H 16		578400	
	H 18		578404	
Prandelli Multyrama Pfm	H 20		578406	
	H 26		578412	
	H 32		578386	
	U 40		578400	
	H 16		578404	
	H 18		578406	
	H 20		578410	
	H 26		578412	
	H 32		578352	
	TH 16		578356	
PURMO Cleverfit Radial	TH 18		578358	
	TH 20		578362	
	TH 26		578364	
	TH 32		578624	
	TH 40		574782	
	TH 16 S (PR-2B)	Mini Z8	574788	
	TH 20 S (PR-2B)	Mini Z8	574794	
	TH 26 S (PR-2B)	Mini Z8	574798	
	TH 32 S (PR-2B)	Mini Z8	578374	
	U 16		578376	
	U 18		578378	
	U 20		578386	
	R	F 16		578456
F 20			578460	
F 26			578462	
F 32			578464	
F 16 S (PR-2B)		Mini Z8	574728	
F 20 S (PR-2B)		Mini Z8	574730	
F 26 S (PR-2B)		Mini Z8	574732	
F 32 S (PR-2B)		Mini Z8	574734	
H 16			578400	
H 20			578406	
H 26			578410	
H 32			578412	
TH 14			578348	
TH 16		578352		
TH 17		578354		
TH 18		578356		
TH 20		578358		
TH 26		578362		
TH 32		578364		
TH 40		578624		
TH 16 S (PR-2B)	Mini Z8	574782		
TH 20 S (PR-2B)	Mini Z8	574788		
TH 26 S (PR-2B)	Mini Z8	574794		
TH 32 S (PR-2B)	Mini Z8	574798		
U 16		578374		
U 20		578378		
U 32		578382		
VP 16		578482		
VP 20		578484		
VP 32		578488		
Raccorderie Metalliche aesPRES ⁴⁾	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
M 18 S (PR-2B)	Mini Z8	574740		
M 22 S (PR-2B)	Mini Z8	574742		
M 28 S (PR-2B)	Mini Z8	574744		
M 35 S (PR-2B)	Mini Z8	574746		

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Raccorderie Metalliche inoxPRES ⁹	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
Raccorderie Metalliche MARINEPRES ⁹	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
Raccorderie Metalliche steelPRES ⁹	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
RBM Tita-fix	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	B 14		578466
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	F 16		578456
	F 18		578458
	F 20		578460
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
RBM Tita-gas	U 20		578378
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
TH 32 S (PR-2B)	Mini Z8	574798	
Redi Nicoll Fluxo	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
TH 20 S (PR-2B)	Mini Z8	574788	
Redi Nicoll Fluxo Gas	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
RIFENG LD PRESS FITTING (F8)	LD 16		578652
RIFENG U PRESS FITTING (F5)	LD 20		578654
	LD 25		578656
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
RIFENG TH PRESS FITTING (F9)	U 25		578380
	U 32		578382
	U 40		578386
	TH 16		578352
	TH 20		578358
	TH 25		578360
RIQUIER A SERTIR	TH 26		578362
	TH 32		578364
	TH 40		578624
	Rfz 12		578490
	Rfz 16		578492
	Rfz 20		578494
	Rfz 25		578496

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Roth PressCheck	RN 14		578434
	RN 16		578454
	RN 17		578436
	RN 20		578438
	RN 25/26		578440
Rubinetteria Bresciane Bonomi TURBO CuNi	RN 32		578442
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
TURBO INOX	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
Rubinetteria Bresciane Bonomi TURBO INOX GAS	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
TURBO STEEL	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	Rubinetteria Bresciane Bonomi TURBO PRESS	M 15	
M 18			578314
M 22			578316
M 28			578318
M 35			578390
M 15 S (PR-2B)		Mini Z8	574738
M 18 S (PR-2B)		Mini Z8	574740
M 22 S (PR-2B)		Mini Z8	574742
M 28 S (PR-2B)		Mini Z8	574744
M 35 S (PR-2B)		Mini Z8	574746
B 14			578466
B 16			578468
B 18			578470
B 20			578472
B 26			578474
B 32		578476	
Rubinetteria Bresciane Bonomi TURBO PRESS GAS	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	
SA.MI plastic Multistrato Gas	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	C 26		578392
	U 32		578382
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	S		
SA.MI plastic	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
SA.MI plastic Multistrato Gas	TH 32 S (PR-2B)	Mini Z8	574798
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
TH 20 S (PR-2B)	Mini Z8	574788	
TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.		
SANHA 3fit-Press Pb-free Serie 25000	B 16		578468	SANHA-NiroSan Industry Presssystem Serie 18000	SA 15		578514		
	B 20		578472		SA 18		578518		
	B 26		578474		SA 22		578520		
	B 32		578476		SA 28		578522		
	F 16		578456		M 15 ¹⁾		578312		
	F 20		578460		M 18 ¹⁾		578314		
	F 26		578462		M 22 ¹⁾		578316		
	F 32		578464		M 28		578318		
	Fz 40		578478		M 35		578390		
	F 16 S (PR-2B)	Mini Z8	574728		M 15 S (PR-2B)	Mini Z8	574738		
	F 20 S (PR-2B)	Mini Z8	574730		M 18 S (PR-2B)	Mini Z8	574740		
	F 26 S (PR-2B)	Mini Z8	574732		M 22 S (PR-2B)	Mini Z8	574742		
	F 32 S (PR-2B)	Mini Z8	574734		M 28 S (PR-2B)	Mini Z8	574744		
	H 16		578400		M 35 S (PR-2B)	Mini Z8	574746		
	H 20		578406		V 15 ¹⁾		578328		
	H 26		578410		V 18 ¹⁾		578332		
	H 32		578412		V 22 ¹⁾		578334		
	TH 16		578352		V 28		578336		
	TH 20		578358		V 35		578604		
	TH 26		578362		V 15 S (PR-2B)	Mini Z8	574752		
	TH 32		578364		V 18 S (PR-2B)	Mini Z8	574756		
	TH 40		578624		V 22 S (PR-2B)	Mini Z8	574758		
	TH 16 S (PR-2B)	Mini Z8	574782		V 28 S (PR-2B)	Mini Z8	574760		
	TH 20 S (PR-2B)	Mini Z8	574788		V 35 S (PR-2B)	Mini Z8	574762		
	TH 26 S (PR-2B)	Mini Z8	574794						
	TH 32 S (PR-2B)	Mini Z8	574798						
	U 16		578374						
	U 20		578378						
	C 26		578392						
	U 32		578382						
	U 40		578386						
	SANHA 3fit-Press PPSU Serie 35000	B 16			578468	SANHA-NiroSan- Presssystem Serie 9000	SA 15		578514
		B 20			578472		SA 18		578518
B 26			578474	SA 22			578520		
B 32			578476	SA 28			578522		
F 16			578456	M 15 ¹⁾			578312		
F 20			578460	M 18 ¹⁾			578314		
F 26			578462	M 22 ¹⁾			578316		
F 32			578464	M 28			578318		
F 16 S (PR-2B)		Mini Z8	574728	M 35			578390		
F 20 S (PR-2B)		Mini Z8	574730	M 15 S (PR-2B)	Mini Z8		574738		
F 26 S (PR-2B)		Mini Z8	574732	M 18 S (PR-2B)	Mini Z8		574740		
F 32 S (PR-2B)		Mini Z8	574734	M 22 S (PR-2B)	Mini Z8		574742		
H 16			578400	M 28 S (PR-2B)	Mini Z8		574744		
H 20			578406	M 35 S (PR-2B)	Mini Z8		574746		
H 26			578410	V 15 ¹⁾			578328		
H 32			578412	V 18 ¹⁾			578332		
TH 16			578352	V 22 ¹⁾			578334		
TH 20			578358	V 28			578336		
TH 26			578362	V 35			578604		
TH 32			578364	V 15 S (PR-2B)	Mini Z8		574752		
TH 16 S (PR-2B)		Mini Z8	574782	V 18 S (PR-2B)	Mini Z8		574756		
TH 20 S (PR-2B)		Mini Z8	574788	V 22 S (PR-2B)	Mini Z8		574758		
TH 26 S (PR-2B)		Mini Z8	574794	V 28 S (PR-2B)	Mini Z8		574760		
TH 32 S (PR-2B)		Mini Z8	574798	V 35 S (PR-2B)	Mini Z8		574762		
U 16			578374						
U 20			578378						
C 26			578392						
U 32			578382						
SANHA Heavy Steel Press		VMP ½" (OD 21,3 mm)		578662	SANHA-NiroSan SF Presssystem Serie 19000 (silicone free)		SA 15		578514
		VMPz ¾" (OD 26,9 mm)		578664			SA 18		578518
SANHA Heavy Steel Press Gas		VMP ½" (OD 21,3 mm)		578662	SA 22			578520	
		VMPz ¾" (OD 26,9 mm)		578664	SA 28			578522	
SANHA-NiroSan Gas Presssystem Serie 17000		SA 15		578514	M 15 ¹⁾			578312	
	SA 18		578518	M 18 ¹⁾		578314			
	SA 22		578520	M 22 ¹⁾		578316			
	SA 28		578522	M 28		578318			
	M 15 ¹⁾		578312	M 35		578390			
	M 18 ¹⁾		578314	M 15 S (PR-2B)	Mini Z8	574738			
	M 22 ¹⁾		578316	M 18 S (PR-2B)	Mini Z8	574740			
	M 28		578318	M 22 S (PR-2B)	Mini Z8	574742			
	M 35		578390	M 28 S (PR-2B)	Mini Z8	574744			
	M 15 S (PR-2B)	Mini Z8	574738	M 35 S (PR-2B)	Mini Z8	574746			
	M 18 S (PR-2B)	Mini Z8	574740	V 15 ¹⁾		578328			
	M 22 S (PR-2B)	Mini Z8	574742	V 18 ¹⁾		578332			
	M 28 S (PR-2B)	Mini Z8	574744	V 22 ¹⁾		578334			
	M 35 S (PR-2B)	Mini Z8	574746	V 28		578336			
	V 15 ¹⁾		578328	V 35		578604			
	V 18 ¹⁾		578332	V 15 S (PR-2B)	Mini Z8	574752			
	V 22 ¹⁾		578334	V 18 S (PR-2B)	Mini Z8	574756			
	V 28		578336	V 22 S (PR-2B)	Mini Z8	574758			
	V 35		578604	V 28 S (PR-2B)	Mini Z8	574760			
	V 15 S (PR-2B)	Mini Z8	574752	V 35 S (PR-2B)	Mini Z8	574762			

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
SANHA NiroTherm Serie 91000	SA 15		578514	
	SA 18		578518	
	SA 22		578520	
	SA 28		578522	
	M 15 ¹⁾		578312	
	M 18 ¹⁾		578314	
	M 22 ¹⁾		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
	V 15 ¹⁾		578328	
	V 18 ¹⁾		578332	
	V 22 ¹⁾		578334	
	V 28		578336	
	V 35		578604	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	SANHA NiroTherm Industry Serie 98000	SA 15		578514
		SA 18		578518
		SA 22		578520
SA 28			578522	
M 15 ¹⁾			578312	
M 18 ¹⁾			578314	
M 22 ¹⁾			578316	
M 28			578318	
M 35			578390	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	
V 15 ¹⁾			578328	
V 18 ¹⁾			578332	
V 22 ¹⁾			578334	
V 28			578336	
V 35			578604	
V 15 S (PR-2B)		Mini Z8	574752	
V 18 S (PR-2B)		Mini Z8	574756	
V 22 S (PR-2B)		Mini Z8	574758	
V 28 S (PR-2B)		Mini Z8	574760	
V 35 S (PR-2B)		Mini Z8	574762	
SANHA-Press Chrom Serie 16000		SA 12		578510
		SA 15		578514
		SA 18		578518
	SA 22		578520	
	SA 28		578522	
	M 12		578310	
	M 15 ¹⁾		578312	
	M 18 ¹⁾		578314	
	M 22 ¹⁾		578316	
	M 28		578318	
	M 12 S (PR-2B)	Mini Z8	574736	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	V 12		578324	
	V 15 ¹⁾		578328	
	V 18 ¹⁾		578332	
	V 22 ¹⁾		578334	
	V 28		578336	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	SANHA-Press GAS Pressfittings Serie 10000/ Serie 11000	SA 12		578510
		SA 14		578512
SA 15			578514	
SA 16			578516	
SA 18			578518	
SA 22			578520	
SA 28			578522	
M 12			578310	
M 15 ¹⁾			578312	
M 18 ¹⁾			578314	
M 22 ¹⁾			578316	
M 28			578318	
M 35			578390	
M 12 S (PR-2B)		Mini Z8	574736	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	
V 12			578324	
V 14			578326	
VG 14			578338	
V 15 ¹⁾			578328	
V 16			578330	
VG 16			578340	
V 18 ¹⁾			578332	
V 22 ¹⁾			578334	
V 28			578336	
V 35			578604	
V 12 S (PR-2B)		Mini Z8	574748	
VG 14 S (PR-2B)		Mini Z8	574750	
V 15 S (PR-2B)		Mini Z8	574752	
VG 16 S (PR-2B)		Mini Z8	574754	
V 18 S (PR-2B)	Mini Z8	574756		
V 22 S (PR-2B)	Mini Z8	574758		
V 28 S (PR-2B)	Mini Z8	574760		
V 35 S (PR-2B)	Mini Z8	574762		

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
SANHA-Press Pressfittings Serie 6000	SA 12		578510
	SA 14		578512
	SA 15		578514
	SA 16		578516
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 12		578310
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	V 12		578324
	V 14		578326
	VG 14		578338
	V 15 ¹⁾		578328
	V 16		578330
	VG 16		578340
	V 18 ¹⁾		578332
	V 22 ¹⁾		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	VG 14 S (PR-2B)	Mini Z8	574750
	V 15 S (PR-2B)	Mini Z8	574752
	VG 16 S (PR-2B)	Mini Z8	574754
V 18 S (PR-2B)	Mini Z8	574756	
V 22 S (PR-2B)	Mini Z8	574758	
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	
SANHA-Press SOLAR Pressfittings Serie 12000/ Serie 13000	SA 12		578510
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 12		578310
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	V 12		578324
	V 15 ¹⁾		578328
	V 18 ¹⁾		578332
	V 22 ¹⁾		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	
SANHA PURAPRESS Serie 8000	SA 12		578510
	SA 14		578512
	SA 15		578514
	SA 16		578516
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 12 ¹⁾		578310
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28 ¹⁾		578318
	M 35 ¹⁾		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	V 12		578324
	V 14		578326
	VG 14		578338
	V 15 ¹⁾		578328
	V 16		578330
	VG 16		578340
	V 18 ¹⁾		578332
	V 22 ¹⁾		578334
V 28		578336	
V 35		578604	
V 12 S (PR-2B)	Mini Z8	574748	
VG 14 S (PR-2B)	Mini Z8	574750	
V 15 S (PR-2B)	Mini Z8	574752	
VG 16 S (PR-2B)	Mini Z8	574754	
V 18 S (PR-2B)	Mini Z8	574756	
V 22 S (PR-2B)	Mini Z8	574758	
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
SANHA-Therm Serie 24000	SA 12		578510	
	SA 15		578514	
	SA 18		578518	
	SA 22		578520	
	SA 28		578522	
	M 12		578310	
	M 15 ¹⁾		578312	
	M 18 ¹⁾		578314	
	M 22 ¹⁾		578316	
	M 28		578318	
	M 35		578390	
	M 12 S (PR-2B)	Mini Z8	574736	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
	V 12		578324	
	V 15 ¹⁾		578328	
	V 18 ¹⁾		578332	
	V 22 ¹⁾		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	SANHA-Therm Industry Serie 28000	SA 12		578510
		SA 15		578514
		SA 18		578518
		SA 22		578520
SA 28			578522	
M 12			578310	
M 15 ¹⁾			578312	
M 18 ¹⁾			578314	
M 22 ¹⁾			578316	
M 28			578318	
M 35			578390	
M 12 S (PR-2B)		Mini Z8	574736	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	
V 12			578324	
V 15 ¹⁾			578328	
V 18 ¹⁾			578332	
V 22 ¹⁾			578334	
V 28			578336	
V 35			578604	
V 12 S (PR-2B)		Mini Z8	574748	
V 15 S (PR-2B)		Mini Z8	574752	
V 18 S (PR-2B)		Mini Z8	574756	
V 22 S (PR-2B)		Mini Z8	574758	
V 28 S (PR-2B)		Mini Z8	574760	
V 35 S (PR-2B)		Mini Z8	574762	
SANITOP PERMATUBO INOX		M 15		578312
		M 18		578314
		M 22		578316
		M 28		578318
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
	SANPRO THPRESS	TH 16		578352
		TH 20		578358
		TH 26		578362
		TH 32		578364
		TH 16 S (PR-2B)	Mini Z8	574782
TH 20 S (PR-2B)		Mini Z8	574788	
TH 26 S (PR-2B)		Mini Z8	574794	
TH 32 S (PR-2B)		Mini Z8	574798	
SATEC SK VITerm	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	U 40		578386	
	SAVEUR REFLEX PEX Water	TH 16		578352
TH 20			578358	
TH 25			578360	
TH 32			578364	

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
SAVEUR REFLEX PEX-AL-PEX Gas	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
Schütz duo-flex tri-o-flex	TH 14		578348	
	TH 16		578352	
	TH 17		578354	
	TH 20		578358	
	TH 25		578360	
	TH 16 S (PR-2B) TH 20 S (PR-2B)	Mini Z8 Mini Z8	574782 574788	
Schwer Fittings AQUApress	M 12		578310	
	M 15		578312	
	M 18		578314	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 12 S (PR-2B)	Mini Z8	574736	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
Seppelfricke VSH SudoPress C-Stahl Visu-Control	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
Seppelfricke VSH SudoPress Edelstahl Visu-Control	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
Seppelfricke VSH SudoPress Kupfer Visu-Control	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
Seppelfricke VSH SudoPress Kupfer Gas Visu-Control	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
Seppelfricke VSH SudoPress Kupfer Solar Visu-Control	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	Seppelfricke VSH XPress C-Stahl	M 12		578310
		M 15		578312
M 18 ¹⁾			578314	
M 22			578316	
M 28 ¹⁾			578318	
M 35			578390	
M 12 S (PR-2B)		Mini Z8	574736	
M 15 S (PR-2B)		Mini Z8	574738	
SAVEUR REFLEX PEX Water	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
Seppelfricke VSH XPress Edelstahl	M 15		578312	
	M 18 ¹⁾		578314	
	M 22		578316	
	M 28 ¹⁾		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
Seppelfricke VSH XPress Edelstahl gas	M 15		578312	
	M 18 ¹⁾		578314	
	M 22		578316	
	M 28 ¹⁾		578318	
	M 35		578390	
Seppelfricke VSH XPress Kupfer	M 12		578310	
	M 15		578312	
	M 18 ¹⁾		578314	
	M 22		578316	
	M 28 ¹⁾		578318	
	M 35		578390	
	M 12 S (PR-2B)	Mini Z8	574736	
	M 15 S (PR-2B)	Mini Z8	574738	
	M 18 S (PR-2B)	Mini Z8	574740	
	M 22 S (PR-2B)	Mini Z8	574742	
Seppelfricke VSH XPress Kupfer gas	M 15		578312	
	M 18 ¹⁾		578314	
	M 22		578316	
	M 28 ¹⁾		578318	
	M 35		578390	
	SESTA SESTA GAS	TH 14		578348
		TH 16		578352
		TH 20		578358
		TH 26		578362
		TH 32		578364
SESTA sistema multistrato	H 16		578400	
	H 20		578406	
	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 26		578362	
	TH 40		578624	
	U 16		578374	
	U 20		578378	
SIGMA LI Premium	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 32 S (PR-2B)	Mini Z8	574798	
	U 16		578374	
	U 20		578378	
	U 25		578380	
SLOVARM PEX-THERM	U 32		578382	
	U 16		578374	
	U 20		578378	
	H 26		578410	
	U 32		578382	
	H 16		578400	
	H 20		578406	
STANDARD HIDRAULICA MultiStandard	H 26		578410	
	H 32		578412	
	Rfz 16		578492	
	Rfz 20		578494	
	Rfz 25		578496	
	Rfz 32		578498	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 32		578364	
steeltrade Presssystem Edelstahl Kontur M	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 32 S (PR-2B)	Mini Z8	574798	
	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
	U 40		578386	
	STELBI Polikraft	M 15		578312
M 18 ¹⁾			578314	
M 22			578316	
M 28 ¹⁾			578318	
M 35			578390	
M 15 S (PR-2B)		Mini Z8	574738	
M 18 S (PR-2B)		Mini Z8	574740	
M 22 S (PR-2B)		Mini Z8	574742	
M 28 S (PR-2B)		Mini Z8	574744	
M 35 S (PR-2B)		Mini Z8	574746	

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
STELBI Stelgas	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
STH Westco COPPER PRESS	M 15		578312	
	M 22		578316	
	M 28		578318	
	M 35		578390	
	M 15 S (PR-2B)	Mini Z8	574738	
TDM BRASS Serie 1600	M 22 S (PR-2B)	Mini Z8	574742	
	M 28 S (PR-2B)	Mini Z8	574744	
	M 35 S (PR-2B)	Mini Z8	574746	
	T			
	H 16		578400	
	H 18		578404	
	H 20		578406	
	H 25		578408	
	H 26		578410	
	H 32		578412	
TH 16		578352		
TH 18		578356		
TH 20		578358		
TH 25		578360		
TH 26		578362		
THL 32		578368		
TH 16 S (PR-2B)	Mini Z8	574782		
TH 20 S (PR-2B)	Mini Z8	574788		
TH 26 S (PR-2B)	Mini Z8	574794		
U 16		578374		
U 18		578376		
U 20		578378		
U 25		578380		
C 26		578392		
U 32		578382		
TDM BRASS Serie 2600	H 16		578400	
	H 18		578404	
	H 20		578406	
	H 25		578408	
	H 26		578410	
	H 32		578412	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 25		578360	
TH 26		578362		
THL 32		578368		
TH 16 S (PR-2B)	Mini Z8	574782		
TH 20 S (PR-2B)	Mini Z8	574788		
TH 26 S (PR-2B)	Mini Z8	574794		
U 16		578374		
U 18		578376		
U 20		578378		
U 25		578380		
C 26		578392		
U 32		578382		
TDM BRASS Serie 1700 gas	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	THL 32		578368	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
TH 26 S (PR-2B)	Mini Z8	574794		
TermoConcept TC-PRESS	Basic E01 ²⁾		578618	
THERMOLUTZ	H 14		578398	
	H 16		578400	
	TH 20		578358	
	TH 20 S (PR-2B)	Mini Z8	574788	
TE-SA TE-SA press serie 800	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
	TH 20 S (PR-2B)	Mini Z8	574788	
	TH 26 S (PR-2B)	Mini Z8	574794	
TH 32 S (PR-2B)	Mini Z8	574798		
THERMACOME ACOPEX ALU	H 16		578400	
	H 20		578406	
	H 26		578410	
	H 32		578412	
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
	TH 32		578364	
	U 16		578374	
	U 20		578378	
TIEMME AL-COBRAPEX Serie 1650	U 32		578382	
	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	THL 32		578368	
	TH 40		578624	
	TH 16 S (PR-2B)	Mini Z8	574782	
TH 20 S (PR-2B)	Mini Z8	574788		
TH 26 S (PR-2B)	Mini Z8	574794		

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
TIEMME Serie 1700 PE-X a pressare	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
TIEMME TIEMME Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	THL 32		578368
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
TIGRE ALPEX GAS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
TKM Systemtechnik	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
TRA MULTITRAPRESS	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
TRA TRAPRESS	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
Tradelink TradePex Crimp Water	K16/P18		578592
	K/20		578594
	K/25		578596
	K32		578598
	K1/40		578600
Tradelink TradePex Crimp Gas	K16/P18		578592
	K/20		578594
	K/25		578596
	K32		578598
	K1/40		578600
TUBIPLAST ITALY MULTILAYER PIPE	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 18		578376
	U 20		578378
	C 26		578392
	U 32		578382
TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	TWEETOP	U 16	
U 20			578378
U 25			578380
U 32			578382
U 40			578386
U			
UNICAL AG MAX-MULTIPEX	U 16		578374
	U 20		578378
	H 26		578410
	C 26		578392
	U 32		578382

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
UNIDELTA DELTA PRESS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
UNIDELTA DELTA PRESS GAS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
U 32		578382	
U 40		578386	
Uponor MLC	UP 14		578576
	UP 16		578578
	UP 18		578580
	UP 20		578582
	UP 25		578584
	UP 32		578586
	U 40		578386
Uponor MLC-D	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586
Uponor MLC-G	UP 20		578582
	UP 25		578584
	UP 32		578586
Uponor S-Press PLUS	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586
Uponor Uni Pipe PLUS	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586
V			
Valsir Bravopress	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	H 32 V		578602
	TH 16		578352
	TH 20		578358
TH 26		578362	
TH 32		578364	
U 16		578374	
U 20		578378	
C 26		578392	
U 32		578382	
Valsir PEXAL	H 14		578398
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	H 32 V		578602
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
U 20		578378	
U 20		578378	
C 26		578392	
U 32		578382	

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Van Marcke NV Tubipex	TH 16		578352
	TH 17		578354
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
Van Marcke NV Tubipress	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
Variotherm System TH	TH 11,6		578344
	TH 16		578352
	TH 20		578358
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	VESBO CARBON	M 15	
M 18			578314
M 22			578316
M 28			578318
M 35			578390
M 15 S (PR-2B)		Mini Z8	574738
M 18 S (PR-2B)		Mini Z8	574740
M 22 S (PR-2B)		Mini Z8	574742
M 28 S (PR-2B)		Mini Z8	574744
M 35 S (PR-2B)		Mini Z8	574746
VESBO INOX	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
VESBO MULTIPRESS TH-U	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 20		578378
VESBO VPREMIUM	C 26		578392
	U 32		578382
	U 16		578374
	U 20		578378
	U 25		578380
Viega Fonterra	U 32		578382
	U 40		578386
	VX 12		578550
	VP 14/15		578480
	VP 16/17		578482
Viega MegaPress (ASTM) ³⁾	VP 20		578484
	VP 25		578486
Viega MegaPress 304 FKM (ASTM) ³⁾	VMP ½" (OD 21,3 mm)		578662
Viega MegaPress 316 FKM (ASTM) ³⁾	VMP ½" (OD 21,3 mm)		578662
Viega MegaPress 316 FKM (ASTM) ³⁾	VMP ½" (OD 21,3 mm)		578662
Viega MegaPress CuNi (ASTM) ³⁾	VMP ½" (OD 21,3 mm)		578662
Viega MegaPress FKM (ASTM) ³⁾	VMP ½" (OD 21,3 mm)		578662
Viega MegaPressG (ASTM) ³⁾	VMP ½" (OD 21,3 mm)		578662
Viega Megapress (EN) ⁴⁾	VMP ¾" (OD 17,2 mm)		578660
	VMP ½" (OD 21,3 mm)		578662
Viega Megapress S (EN) ⁴⁾	VMP ¾" (OD 17,2 mm)		578660
	VMP ½" (OD 21,3 mm)		578662
	VX 16		578552
	VX 20		578554
Viega Pexfit Fosta G	VX 25		578556
	VX 16		578552
	VX 20		578554
Viega Prestabo	VX 25		578556
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
V 28 S (PR-2B)	Mini Z8	574760	

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
Viega Profipress	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	Viega Profipress G	V 12		578324
		V 15		578328
		V 18		578332
V 22			578334	
V 28			578336	
V 35			578604	
V 12 S (PR-2B)		Mini Z8	574748	
V 15 S (PR-2B)		Mini Z8	574752	
V 18 S (PR-2B)		Mini Z8	574756	
V 22 S (PR-2B)		Mini Z8	574758	
V 28 S (PR-2B)		Mini Z8	574760	
V 35 S (PR-2B)		Mini Z8	574762	
Viega Profipress S		V 12		578324
		V 15		578328
		V 18		578332
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	Viega Profipress Therm	V 12		578324
		V 15		578328
		V 18		578332
V 22			578334	
V 12 S (PR-2B)		Mini Z8	574748	
V 15 S (PR-2B)		Mini Z8	574752	
Viega ProPress (ASTM) ³⁾	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	VUS ½" (OD 15,9 mm)		578566	
Viega ProPress 304 FKM (ASTM) ³⁾	VUS ¾" (OD 22,2 mm)		578568	
	VUS 1" (OD 28,6 mm)		578570	
	VUS 1¼" (OD 34,9 mm)		578606	
	VUS ½" (OD 15,9 mm)		578566	
	VUS ¾" (OD 22,2 mm)		578568	
Viega ProPress 316 (ASTM) ³⁾	VUS 1" (OD 28,6 mm)		578570	
	VUS 1¼" (OD 34,9 mm)		578606	
	VUS ½" (OD 15,9 mm)		578566	
	VUS ¾" (OD 22,2 mm)		578568	
	VUS 1" (OD 28,6 mm)		578570	
Viega ProPress WATER System AUS	VUS 1¼" (OD 34,9 mm)		578606	
	VAU 15 (OD 12,7 mm)		578630	
	VAU 20 (OD 19,1 mm)		578632	
	VAU 25 (OD 25,4 mm)		578634	
Viega ProPressG GAS System AUS	VAU 32 (OD 31,8 mm)		578636	
	VAU 15 (OD 12,7 mm)		578630	
	VAU 20 (OD 19,1 mm)		578632	
Viega Raxinox	VAU 25 (OD 25,4 mm)		578634	
	VAU 32 (OD 31,8 mm)		578636	
	VRX 16		578640	
	VRX 20		578642	
Viega Raxofix	VRX 16		578640	
	VRX 20		578642	
	VRX 25		578644	
	VRX 32		578646	
Viega Sanfix	VP 16/17		578482	
	VP 20		578484	
	VP 25		578486	
	VP 32		578488	
Viega Sanfix Fosta	VP 16/17		578482	
	VP 20		578484	
	VP 25		578486	
	VP 32		578488	
Viega Sanpress	VP 16/17		578482	
	VP 20		578484	
	VP 25		578486	
	VP 32		578488	
	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
V 35		578604		
Viega Sanpress Inox	V 12 S (PR-2B)	Mini Z8	574748	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
	V 28 S (PR-2B)	Mini Z8	574760	
	V 35 S (PR-2B)	Mini Z8	574762	
	V 12		578324	
	V 15		578328	
	V 18		578332	
	V 22		578334	
	V 28		578336	
	V 35		578604	
	V 15 S (PR-2B)	Mini Z8	574752	
	V 18 S (PR-2B)	Mini Z8	574756	
	V 22 S (PR-2B)	Mini Z8	574758	
V 28 S (PR-2B)	Mini Z8	574760		
V 35 S (PR-2B)	Mini Z8	574762		

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Viega Sanpress Inox G	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
V 35 S (PR-2B)	Mini Z8	574762	
Viega Smartpress	VX 16		578552
	VX 20		578554
	VX 25		578556
Viessmann	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
Vogel & Noot EASYTEC	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
VSH MultiPress	U 14		578372
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 32 S (PR-2B)	Mini Z8	574798
VSH MultiPress Gas	U 16		578374
	U 20		578378
	U 25		578380
	TH 16		578352
	TH 20		578358
VSH SudoPress Carbon	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 32 S (PR-2B)	Mini Z8	574798
	V 12		578324
	V 15		578328
VSH SudoPress Copper	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 S (PR-2B)	Mini Z8	574748
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
	V 12		578324
	V 14		578326
	V 15		578328
V 16		578330	
V 18		578332	
V 22		578334	
V 28		578336	
V 35		578604	
V 12 S (PR-2B)	Mini Z8	574748	
V 14 S (PR-2B)	Mini Z8	574800	
V 15 S (PR-2B)	Mini Z8	574752	
V 16 S (PR-2B)	Mini Z8	574802	
V 18 S (PR-2B)	Mini Z8	574756	
V 22 S (PR-2B)	Mini Z8	574758	
V 28 S (PR-2B)	Mini Z8	574760	
V 35 S (PR-2B)	Mini Z8	574762	

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
VSH SudoPress Copper Gas	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
V 35		578604	
VSH SudoPress Stainless	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
VSH XPress Carbon	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
VSH XPress Copper	M 12		578310
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574736
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
VSH XPress Copper GAS	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	M 12		578310
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 12 S (PR-2B)	Mini Z8	574738
	M 15 S (PR-2B)	Mini Z8	574740
VSH XPress Stainless Gas	M 18 S (PR-2B)	Mini Z8	574742
	M 22 S (PR-2B)	Mini Z8	574744
	M 28 S (PR-2B)	Mini Z8	574746
	M 35 S (PR-2B)	Mini Z8	574748
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
W	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
Watts MTR Art press	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
WATTS RADIANT Watts WaterPEX	US ¾"		578534
	US ½"		578536
	US ¾"		578538
WATTS RADIANT Watts	US ¾"		578534
	US ½"		578536
	US ¾"		578538
Watts RadiantPEX	US 1"		578540
	US ¾"		578540

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
WATTS	U 16 (1/2")		578374
RADIANT	U 20 (5/8")		578378
Watts	U 25 (3/4")		578380
RadiantPEX-AL	U 32 (1")		578382
Wavin	B 16		578468
Tigris K5/M5	B 20		578472
	B 32		578476
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	TH 40		578624
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586
WEECON	M 15		578312
PRESS-C-Stahl	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
WEECON	M 15		578312
PRESS-Edelstahl	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 S (PR-2B)	Mini Z8	574738
	M 18 S (PR-2B)	Mini Z8	574740
	M 22 S (PR-2B)	Mini Z8	574742
	M 28 S (PR-2B)	Mini Z8	574744
	M 35 S (PR-2B)	Mini Z8	574746
WEECON	V 15		578328
PRESS-Kupfer	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 S (PR-2B)	Mini Z8	574752
	V 18 S (PR-2B)	Mini Z8	574756
	V 22 S (PR-2B)	Mini Z8	574758
	V 28 S (PR-2B)	Mini Z8	574760
	V 35 S (PR-2B)	Mini Z8	574762
WEM	U 16		578374
WIELAND	TH 14		578348
cuprotherm	TH 16		578352
CTX	TH 18		578356
	TH 20		578358
	TH 26		578362

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
WKS-Press	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
WÜRTH	TH 16		578352
Würth	TH 20		578358
	TH 26		578362
	HE 32		578370
X			
XtraConnect	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 S (PR-2B)	Mini Z8	574728
	F 20 S (PR-2B)	Mini Z8	574730
	F 26 S (PR-2B)	Mini Z8	574732
	F 32 S (PR-2B)	Mini Z8	574734
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16 S (PR-2B)	Mini Z8	574782
	TH 20 S (PR-2B)	Mini Z8	574788
	TH 26 S (PR-2B)	Mini Z8	574794
	TH 32 S (PR-2B)	Mini Z8	574798
	U 16		578374
	U 20		578378
(DN 26)	U 25		578380
	U 32		578382
	VP 16		578482
	VP 20		578484
	VP 32		578488
Y			
YX COPPER	Yz 16 UNI		578740
UNIPEX Water & Gas (AUS)	Yz 20 UNI		578742
	Yz 25 UNI		578744
	Yz 32 UNI		578746
Z			
ZEWOTHERM	TH 12		578346
Zewo Press Premium	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
ZEWOTHERM	TH 16		578352
Zewo Press PPSU	TH 20		578358
	TH 26		578362
	TH 32		578364
ZURN	US 3/8"		578534
INDUSTRIES	US 1/2"		578536
ZURN PEX	US 3/4"		578538
	US 1"		578540

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For taking suitable pressing inserts.
- Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

The suitability of REMS pressing tools for pressfitting systems: Date 12.10.2022. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 180 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

Accessories

Description	Art.-No.
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700
Steel case with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516
L-Boxx system case with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704
Steel case with insert for 8 pressing tongs Mini/cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295
L-Boxx system case with insert for 11 pressing tongs Mini and 6 pressing rings S (PR-2B)	578659



REMS cropping tongs Mini

Accessories for REMS radial presses 22 kN

High performance cropping tongs Mini in forged and specially hardened steel for cutting threaded rods.

Steel, stainless steel up to
hardness classification 4.8 (400 N/mm²) M 6 – M 10

REMS cropping tongs Mini – cuts in just 2 seconds!

Made of forged and specially hardened steel.



Reversible cropping inserts for double service life.

M cropping inserts with high precision thread contour machined on CNC machining centres for exact guiding of the threaded rod in the cutting process. Pliers parts, cropping inserts and specially machined and hardened cutting edges, made to fit exactly, for cutting without burr.

Threaded rod can be screwed into a threaded connection of the pipe clip or the nut without rework after cutting.

Cutting device in pliers design (**Patent EP 1 459 825, patent US 7,284,330**). Very compact design and low weight of the REMS Mini cropping tongs due to special arrangement of the cropping tongs connection (**Patent EP 1 952 948**). Recesses in the connecting plate for safe guidance of the connecting lugs for offset-free pressing (**Patent EP 2 347 862**).

Can be driven by all REMS radial presses 22 kN.



German Quality Product



Patent EP 1 952 948
Patent EP 1 459 825
Patent US 7,284,330
Patent EP 2 347 862

Supply format

REMS cropping tongs Mini. Cropping tongs with 1 pair of reversible cropping inserts for steel, stainless steel, M 6 – M 10. In a carton.

Description	for threaded rods	Art.-No.	
REMS cropping tongs Mini M 6	M 6	578620	
REMS cropping tongs Mini M 8	M 8	578621	
REMS cropping tongs Mini M 10	M 10	578622	

Accessories

Description	for threaded rods	Art.-No.	
Cropping inserts M 6 (pair)	M 6	571891	
Cropping inserts M 8 (pair)	M 8	571896	
Cropping inserts M 10 (pair)	M 10	571866	
Steel case with insert for 8 pressing tongs Mini/cropping tongs Mini and compartment for pipe cutter up to 42 mm		578295	

