REMS special saw blades

Accessories for REMS Tiger/VE/SR, Tiger pneumatic, Tiger 22V VE and other makes

Special saw blades for right angle sawing and for fast dismantling of steel pipes with power transmitting guide support.

Steel pipes

REMS special saw blades – for right-angled sawing with force-transmitting guide holder, for 400% more sawing power.

Specially developed for REMS Tiger.

Absolutely essential for right angle sawing and for fast dismantling with power transmitting guide support. This produces multiple thrust pressure by a five-fold force-transmitting leverage, for 400% more sawing power. Normal saw blades with single tang do not withstand the high feed pressure during sawing with guide support, they break at the mounting point.

For this reason, extra thick REMS special saw blade, resistant to bending and distortion.

Double tang mounting with exceptionally wide clamping face ensures accurate seating and high stability.

Coarse, corrugated tooth pattern for rapid sawing. Long service life.



German Qualit	y Product
---------------	-----------

, , , , , , , , , , , , , , , , , , , ,								<u> </u>	
REMS special saw blades → REMS Tiger, etc.	Ø inches/ Length mm	Tooth pitch mm	Material*	Teeth	Colour			ArtNo.	€
REMS special saw blade 2"/140-2.5 steel pipes ≤ 2"	2"/140	2.5	HSS-Bi		yellow	5		561007 R05	64,40
REMS special saw blade 2"/140-3.2 steel pipes ≤ 2"	2"/140	3.2	HSS-Bi		yellow	5	REMS CASE	561001 R05	60,10
REMS special saw blade 4"/200-3.2 steel pipes ≤ 4"	4"/200	3.2	HSS-Bi		yellow	5	REMS WE'S C	561002 R05	79,70
REMS special saw blade 6"/260-3.2 steel pipes ≤ 6"	6"/260	3.2	HSS-Bi		yellow	5		561008R05	103,10

For hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes, use the finer toothed REMS universal saw blade

instead of the REMS special saw blade in combination with REMS Tiger SR with electronic speed regulation (page 71).

REMS universal saw blades

Universal saw blade for free-hand sawing and for sawing with power transmitting guide support. Instead of many different saw blades.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Highly flexible, also ideal for sawing flush with the wall.

REMS universal saw blades - for all sawing jobs.

Only 1 universal saw blade instead of many different saw blades for all sawing jobs. Resilient material, highly flexible, also for flush-to-wall sawing.

Double tang mounting with exceptionally wide clamping face for accurate seating and high stability. Also for sawing with power transmitting guide support. Single tang saw blades are unable to cope with the high thrust pressure when sawing with a guide holder, they break at the clamping point.


Alternating tooth pitch (combi-teeth) for fast, smooth cut, very highly hardened in the teeth area. Straight-set teeth.

Thus outstanding cutting performance and prolonged service life.



Accessories for REMS Cat VE, Tiger/VE/SR,

Cat 22 V VE and other makes



Universal

Double tand









Cormon Quality Broduct

German Quality Product				ι		<u> </u>		526) (200) (
REMS universal saw blades → REMS Tiger, REMS Cat, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour			ArtNo.	€
REMS universal saw blade 100-1.8/2.5 for all sawing work	100	Combo 1.8/2.5	HSS-Bi flexible	,2225	red	5		561006 R05	41,40
REMS universal saw blade 150-1.8/2.5 for all sawing work	150	Combo 1.8/2.5	HSS-Bi flexible	,2225;	red	5		561005 R05	59,20
REMS universal saw blade 200-1.8/2.5 for all sawing work	200	Combo 1.8/2.5	HSS-Bi flexible	,2225	red	5	REMS Development of the state o	561003R05	78,40
REMS universal saw blade 300-1.8/2.5 for all sawing work	300	Combo 1.8/2.5	HSS-Bi flexible	,2225	red	5	REMS Data of State State States Street Street	561004R05	116,00

Also for nail-embedded wood, pallets. For hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes, lower speed required, e.g. by using REMS Tiger SR with electronic speed regulation (page 71).

Accessories for all REMS reciprocating saws and other makes

Saw blades for free-hand sawing for different materials.

Alternating tooth pitch (combi-teeth) for fast, smooth cut, also when sawing mixed materials (wood/metal).

Flexible saw blades, also for sawing flush with wall.

Corrugated teeth for smooth cut with low tooth pitch.

Straight-set teeth for aggressive cut with coarse tooth pitch.

• Straight teeth for saw blades with very wide carbide teeth.

Carbide-granulate for materials that are difficult to cut.

REMS saw blades for metal	Length	Tooth	Material*	Teeth	Colour			ArtNo.	€
➔ REMS Puma, REMS Cat, REMS Tiger, etc.	mm	pitch mm							
REMS saw blade 150-1			HSS-Bi				REMS KIR		
sheet metal, metal, also stainless steel, ≥ 1.2 mm	150	1	flexible		red	5		561105R05	26,70
REMS saw blade 200-1			HSS-Bi						
sheet metal, metal, also stainless steel, ≥ 1.2 mm	200	1	flexible		red	5		561106 R05	35,00
REMS saw blade 90-1.4, curved blade							-		
metal, also stainless steel, ≥ 1.5 mm	90	1.4	HSS-Bi		red	5		561107 R05	24,80
REMS saw blade 150-1.4			HSS-Bi						
metal, also stainless steel, ≥ 1.5 mm	150	1.4	flexible		red	5		561104R05	27,90
REMS saw blade 200-1.4			HSS-Bi				REMS @@		
metal, also stainless steel, ≥ 1.5 mm	200	1.4	flexible		red	5	Recording for the second second	561108 R05	35,20
REMS saw blade 100-1.8			HSS-Bi				REMS 20		
metal, also stainless steel, ≥ 2 mm	100	1.8	flexible		red	5	A CONTRACTOR OF A CONTRACTOR OFTA CONTRACTOR O	561101 R05	23,90
REMS saw blade 150-1.8			HSS-Bi				REMS 20		
metal, also stainless steel, ≥ 2 mm	150	1.8	flexible		red	5	Contraction of the section of the se	561103R05	27,90
REMS saw blade 200-1.8			HSS-Bi			<u> </u>	REMS (AC)		
metal, also stainless steel, ≥ 2 mm	200	1.8	flexible		red	5		561102 R05	35,00
REMS saw blade 200-2.5			HSS-Bi			1	REMS Ø		
metal, also stainless steel, ≥ 3 mm	200	2.5	flexible	•>>>>;	red	5		561109 R05	35,00
REMS saw blade 280-2.5			HSS-Bi			1	REMS ØR		
metal, also stainless steel, ≥ 3 mm	280	2.5	flexible	·>>>>>	red	5	And the second second second	561112R05	44.30

German Quality Product									
REMS saw blades for wood and metal → REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour			ArtNo.	€
REMS saw blade 210-1.8/2.5 round tip, no sticking pallets, wood, wood with nails, metal ≥ 2.5 mm	210	Combo 1.8/2.5	HSS-Bi flexible	,2225;	black	5	REMS TEN 200	561113R05	36,00
REMS saw blade 150-2.5 wood, wood with nails, pallets, metal ≥ 3 mm	150	2.5	HSS-Bi flexible	,9999;	black	5		561110R05	26,70
REMS saw blade 225-2.5 , extra thick, for disassembly wood, wood with nails, metal ≥ 3 mm	225	2.5	HSS-Bi		black	3	REMS 200	561114 R03	34,30
REMS saw blade 300-2.5 , extra thick, for disassembly wood, wood with nails, metal ≥ 3 mm	300	2.5	HSS-Bi		black	3	REMS 200	561116R03	45,70
REMS saw blade 300-4.2 wood	300	4.2	WS	·2>2>;	black	5	REMS 🖾 🗸	561111 R05	32,60
REMS saw blade 225-3.2/5.0 wood, wood with nails	225	Combo 3.2/5.0	HSS-Bi flexible	12223	black	5	REMS @ 20	561117R05	40,70
REMS saw blade 290-5.0/6.35 green wood	290	Combo 5.0/6.35	WS	·>>>>;	black	5	REMS 12	561118R05	44,30
REMS saw blade 150-6.35 wood	150	6.35	ws	·>>>>;	black	5	REMS B	561119R05	18,90

REMS saw blades for different purposes → REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour			ArtNo.	€
REMS saw blade 150-4.2 breeze blocks, plasterboard	150	4.2	WS	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	white	5	REMS	561115R05	23,40
REMS saw blade 225-8.5 breeze blocks, hard wood	225	8.5	НМ	·>>>;	white	1	REMS DE	561120R01	60,60
REMS saw blade 300-8.5 breeze blocks, hard wood	300	8.5	НМ	·>>>>;	white	1	Communication of the Communica	561121 R01	72,70
REMS saw blade 400-8.5 breeze blocks, hard wood	400	8.5	НМ	·2>2>;	white	1	Constanting Management	561122 R01	105,00
REMS saw blade 235-12 breeze blocks, pumice, brick	235	12	НМ		white	1	REMS D	561123R01	84,40
REMS saw blade 300-12 breeze blocks, pumice, brick	300	12	НМ		white	1	REMS OF LOW CONTRACT	561124R01	97,70
REMS saw blade 300-12, extra high blade breeze blocks, pumice, brick	300	12	НМ		white	1	REMS	561125R01	116,00
REMS saw blade 200 cast iron etc.	200		HM-G		white	2	REMS 38	561126 R02	34,90

